

## 4MP HD Smart Dual Light Fixed Bullet Network Camera EC-B4F28UDL



## Features

- High quality image with 4 MP, 1/3" CMOS sensor
- 4 MP (2560 × 1440)@25/20 fps; 3 MP (2304 × 1296)@30/25 fps; 1080P (1920 × 1080)@30/25 fps
- Smart dual-light ensures high quality image
- Ultra 265, H.265, H.264
- Supports ultra motion detection
- Built-in mic
- Up to 30 m (98.4 ft.) IR and warm light distance
- MicroSD, up to 512 GB
- IP67 protection
- 3-axis
- Supports PoE power supply
- Supports corridor mode

## Specifications

| Model                              | EC-B4F28UDL                                                                                                                                                                                                                                       |
|------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Camera</b>                      |                                                                                                                                                                                                                                                   |
| Max Resolution                     | 4 MP                                                                                                                                                                                                                                              |
| Sensor                             | 1/3.0" CMOS                                                                                                                                                                                                                                       |
| Min. Illumination                  | Color: 0.01 Lux (F1.6, AGC ON), 0 Lux with light                                                                                                                                                                                                  |
| Day/Night                          | IR-cut filter with auto switch (ICR)                                                                                                                                                                                                              |
| Shutter                            | Auto/Manual, 1 ~ 1/100000s                                                                                                                                                                                                                        |
| Adjustment Angle                   | Pan: 0° to 360°, Tilt: 0° to 90°, Rotate: 0° to 360°                                                                                                                                                                                              |
| S/N                                | >52 dB                                                                                                                                                                                                                                            |
| WDR                                | DWDR                                                                                                                                                                                                                                              |
| <b>Lens</b>                        |                                                                                                                                                                                                                                                   |
| Focal Length                       | 2.8 mm                                                                                                                                                                                                                                            |
| Iris Type                          | Fixed                                                                                                                                                                                                                                             |
| Iris                               | F1.6                                                                                                                                                                                                                                              |
| Field of View (H)                  | 93.2°                                                                                                                                                                                                                                             |
| Field of View (V)                  | 51.5°                                                                                                                                                                                                                                             |
| Field of View (D)                  | 108.0°                                                                                                                                                                                                                                            |
| Lens Type                          | Fixed                                                                                                                                                                                                                                             |
| <b>DORI</b>                        |                                                                                                                                                                                                                                                   |
| DORI Distance (Lens)               | 2.8 mm                                                                                                                                                                                                                                            |
| DORI Distance (Detect)             | 63.0 m (206.7 ft.)                                                                                                                                                                                                                                |
| DORI Distance (Observe)            | 25.2 m (82.7 ft.)                                                                                                                                                                                                                                 |
| DORI Distance (Recognize)          | 12.6 m (41.3 ft.)                                                                                                                                                                                                                                 |
| DORI Distance (Identify)           | 6.3 m (20.7 ft.)                                                                                                                                                                                                                                  |
| <b>Illuminator</b>                 |                                                                                                                                                                                                                                                   |
| Supplemental Light                 | Dual light                                                                                                                                                                                                                                        |
| Illumination Distance (IR)         | 30 m (98.4 ft.)                                                                                                                                                                                                                                   |
| Illumination Distance (Warm Light) | 30 m (98.4 ft.)                                                                                                                                                                                                                                   |
| Wavelength                         | 850 nm                                                                                                                                                                                                                                            |
| <b>Video</b>                       |                                                                                                                                                                                                                                                   |
| Video Compression                  | Ultra 265, H.265, H.264                                                                                                                                                                                                                           |
| H.264 Code Profile                 | Baseline profile, Main profile, High profile                                                                                                                                                                                                      |
| Frame Rate                         | Main Stream: 4 MP (2560 × 1440), max. 25 fps; 3 MP (2304 × 1296), max. 30 fps; 1080P (1920 × 1080), max. 30 fps;<br>Sub Stream: D1 (720 × 576), max. 30 fps; 640 × 360, max. 30 fps; 2CIF (704 × 288), max. 30 fps; CIF (352 × 288), max. 30 fps; |
| Video Bit Rate                     | 128 Kbps to 6144 Kbps                                                                                                                                                                                                                             |
| U-code                             | Support                                                                                                                                                                                                                                           |
| OSD                                | Up to 4 OSDs                                                                                                                                                                                                                                      |
| Privacy Mask                       | Up to 4 areas                                                                                                                                                                                                                                     |


|                         |                                                                                                                                                                                                            |
|-------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ROI                     | Support                                                                                                                                                                                                    |
| Video Stream            | Dual streams                                                                                                                                                                                               |
| Image                   |                                                                                                                                                                                                            |
| White Balance           | Auto, Outdoor, Fine tune, Sodium lamp, Locked, Auto2, Area white balance                                                                                                                                   |
| Digital Noise Reduction | 2D/3D DNR                                                                                                                                                                                                  |
| Smart IR                | Support                                                                                                                                                                                                    |
| Flip                    | Normal, Flip vertical, Flip horizontal, 180°, 90° Clockwise, 90° Anti-clockwise                                                                                                                            |
| Dewarping               | N/A                                                                                                                                                                                                        |
| HLC                     | Support                                                                                                                                                                                                    |
| BLC                     | Support                                                                                                                                                                                                    |
| Defog                   | Digital defog                                                                                                                                                                                              |
| Image Stabilization     | N/A                                                                                                                                                                                                        |
| Events                  |                                                                                                                                                                                                            |
| Basic Detection         | Ultra motion detection, Motion detection, Audio detection, Tampering alarm                                                                                                                                 |
| General Function        | Watermark, IP address filtering, Access policy, ARP protection, RTSP authentication, User authentication, HTTP authentication                                                                              |
| Audio                   |                                                                                                                                                                                                            |
| Audio Compression       | AAC-LC, G.711U, G.711A                                                                                                                                                                                     |
| Audio Bitrate           | G.711U/G.711A: 64 kbps, AAC-LC: 128 kbps                                                                                                                                                                   |
| Two-way Audio           | N/A                                                                                                                                                                                                        |
| Suppression             | Support                                                                                                                                                                                                    |
| Sampling Rate           | G.711U/G.711A: 8 kHz, AAC-LC: 8 kHz, 16 kHz, 48 kHz                                                                                                                                                        |
| Storage                 |                                                                                                                                                                                                            |
| Edge Storage            | MicroSD, up to 512 GB                                                                                                                                                                                      |
| Network Storage         | ANR, NAS (NFS)                                                                                                                                                                                             |
| Network                 |                                                                                                                                                                                                            |
| Protocols               | IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, UPnP, HTTP, HTTPS, QoS, SSL/TLS, SNMP                                                                                        |
| Compatible Integration  | API, SDK                                                                                                                                                                                                   |
| User/Host               | Up to 32 users. 3 user levels: administrator, common user and operator                                                                                                                                     |
| Security                | Password Protection, Strong Password, HTTPS Encryption, Export Operation Logs, Basic and Digest Authentication for RTSP, Digest Authentication for HTTP, TLS 1.2, WSSE and Digest Authentication for ONVIF |
| Client                  | EZStation, APP                                                                                                                                                                                             |
| Web Browser             | Plug-in required live view: IE 10+, Chrome 45+, Firefox 52+, Edge 79+, Plug-in free live view: Chrome 57+, Firefox 58+, Edge 16+                                                                           |
| Interface               |                                                                                                                                                                                                            |
| Audio I/O               | N/A                                                                                                                                                                                                        |
| Alarm I/O               | N/A                                                                                                                                                                                                        |
| Serial Port             | N/A                                                                                                                                                                                                        |
| Built-in Mic            | Support                                                                                                                                                                                                    |
| Built-in Speaker        | N/A                                                                                                                                                                                                        |
| WIFI                    | N/A                                                                                                                                                                                                        |

|                     |                                                                                            |
|---------------------|--------------------------------------------------------------------------------------------|
| Network             | 1 × RJ45 10 M/100 M Base-TX Ethernet                                                       |
| Video Output        | N/A                                                                                        |
| Certification       |                                                                                            |
| EMC                 | CE-EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 50130-4)<br>FCC (FCC 47 CFR part15 B) |
| Safety              | CE LVD (EN 62368 1)<br>UL/CUL (UL 62368 1, CAN/CSA C22.2 No. 62368 1)                      |
| Environment         | CE-RoHS (2011/65/EU;(EU)2015/863); WEEE (2012/19/EU);                                      |
| Protection          | IP67 (IEC 60529)                                                                           |
| General             |                                                                                            |
| Power               | DC 12 V±25%, PoE (IEEE 802.3af)                                                            |
| Power Consumption   | Max. 4.5 W                                                                                 |
| Power Interface     | Ø5.5 mm coaxial power plug                                                                 |
| Dimensions          | 161.4 mm × 66.1 mm × 66.3 mm (6.3" × 2.6" × 2.6") (L × W × H)                              |
| Weight              | 0.21 kg (0.46 lb.)                                                                         |
| Material            | Metal + Plastic                                                                            |
| Storage Environment | -30 °C to 60 °C (-22 °F to 140 °F), Humidity: ≤ 95% RH (non-condensing)                    |
| Working Environment | -30 °C to 60 °C (-22 °F to 140 °F), Humidity: ≤ 95% RH (non-condensing)                    |
| Surge Protection    | 4 KV                                                                                       |
| Reset Button        | Support                                                                                    |
| Web Client Language | 4 Languages: English, Russian, Spanish, Vietnamese                                         |




Dimensions

68:C6:AC:6F:9A:BE, DESKTOP-40J26M6

68:C6:AC:6F:9A:BE, DESKTY




68:C6:AC:6F:9A:BE, DESKTY



68:C6:AC:6F:9A:BE, DESKTY

68:C6:AC:6F:9A:BE, DESKTOP-40J26M6



68:C6:AC:6F:9A:BE, DESKTY

# Unlimited New View

## Zhejiang Uniview Technologies Co., Ltd.



<http://www.uniview.com>



[overseasbusiness@uniview.com](mailto:overseasbusiness@uniview.com); [globalsupport@uniview.com](mailto:globalsupport@uniview.com)



No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China



©2026 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

\*Product specifications and availability are subject to change without notice.

Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.