

2MP Wise-ISP Fixed Warm Light Dome Network Camera IPC3522LE-ADF28(40)K-WP2



Features

- High quality image with 1080P, 1/2.8" CMOS sensor and F1.0 large aperture lens
- 1080P (1920 × 1080)@30/25 fps; 720P (1280 × 720)@30/25 fps
- Ultra 265, H.265, H.264, MJPEG(Sub Stream Only)
- Supports Wise-ISP technology, deeply optimizing color, detail, and smear effects in extremely low-light scenes
- Support cross line, intrusion detection (based on human body detection and vehicle detection)
- Support ultra motion detection (human/ vehicle detection)
- 120 dB true WDR technology enables clear image in strong light scene
- Supports 9:16 corridor mode
- Built-in mic
- Warm light, up to 30 m (98.4 ft.) warm light distance
- MicroSD, up to 512 GB
- IP67 protection and IK10 protection
- Supports PoE power supply



Specifications

Model	IPC3522LE-ADF28K-WP2		IPC3522LE-ADF40K-WP2	
Camera				
Max Resolution	2 MP			
Sensor	1/2.8" CMOS			
Min. Illumination	Color: 0.0003 Lux (F1.0, AGC ON)			
Shutter	Auto/Manual, 1 to 1/100000 s			
Adjustment Angle	Pan: 8° to 360°, Tilt: 0° to 68°, Rotate: 10° to 360°			
S/N	> 52 dB			
WDR	120 dB			
Lens				
Focal Length	2.8 mm		4.0 mm	
Iris	F1.0			
Field of View (H)	111.2 °		86.2 °	
Field of View (V)	61.1 °		46.6 °	
Field of View (D)	126.6 °		98.1 °	
Lens Type	Fixed			
Iris Type	Fixed			
DORI				
DORI Distance (Lens)	2.8 mm		4.0 mm	
DORI Distance (Detect)	43.4 m (142.5 ft.)		62.1 m (203.6 ft.)	
DORI Distance (Observe)	17.4 m (57.0 ft.)		24.8 m (81.4 ft.)	
DORI Distance (Recognize)	8.7 m (28.5 ft.)		12.4 m (40.7 ft.)	
DORI Distance (Identify)	4.3 m (14.3 ft.)		6.2 m (20.4 ft.)	
Illuminator				
Illumination Distance (Warm Light)	30 m (98.4 ft.)			
Light On/Off Control	Auto/Manual			
Supplemental Light	Warm light			
Video				
Video Compression	Ultra 265, H.265, H.264, MJPEG (Sub Stream Only)			
H.264 Code Profile	Baseline profile, Main profile, High profile			
Frame Rate	Main Stream: 1080P (1920 × 1080), max. 30 fps; 720P (1280 × 720), max. 30 fps; Sub Stream: 720P (1280 × 720), max. 30 fps; D1 (720 × 576), max. 30 fps; 640 × 360, max. 30 fps; 2CIF (704 × 288), max. 30 fps; CIF (352 × 288), max. 30 fps;			
Video Bit Rate	128 Kbps to 6144 Kbps			
OSD	Up to 4 OSDs			
Privacy Mask	Up to 4 areas			
ROI	Up to 8 areas			
U-code	Support			
Video Stream	Dual streams			
Snapshot	Support			

Image	
Smart Illumination	Support
White Balance	Auto, Outdoor, Fine tune, Sodium lamp, Locked, Auto2, Area white balance
Digital Noise Reduction	2D/3D DNR
Flip	Normal, Flip vertical, Flip horizontal, 180°, 90° Clockwise, 90° Anti-clockwise
HLC	Support
Dewarping	N/A
BLC	Support
Defog	Digital defog
Intelligent	
Smart Intrusion Prevention (Lite)	Intrusion, crossline detection (both detection are based on human body and vehicle detection)
Events	
Basic Detection	Motion detection, Ultra motion detection (based on human body and vehicle detection), Tampering alarm, Audio detection
General Function	Watermark, IP address filtering, Access policy, ARP protection, RTSP authentication, User authentication, HTTP authentication
Audio	
Audio Compression	G.711U, G.711A, AAC-LC
Audio Bitrate	G.711U/G.711A: 64 kbps, AAC-LC: 128 kbps
Two-way Audio	N/A
Suppression	Support
Sampling Rate	G.711U/G.711A: 8 kHz, AAC-LC: 8 kHz, 16 kHz, 48 kHz
Storage	
Edge Storage	MicroSD, up to 512 GB
Network Storage	ANR, NAS (NFS)
Network	
Protocols	IPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP, SSL/TLS
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API, SDK
Client	EZStation, APP
Web Browser	Plug-in required live view: IE 10+, Chrome 45+, Firefox 52+, Edge 79+, Plug-in free live view: Chrome 57+, Firefox 58+, Edge 16+
Security	Password protection, Strong Password, HTTPS encryption, Export operation logs, Basic and Digest Authentication for RTSP, Digest Authentication for HTTP, TLS 1.2, WSSE and Digest Authentication for ONVIF
User/Host	Up to 32 users. 2 user levels: administrator and common user
Interface	
Audio I/O	N/A
Alarm I/O	N/A
Serial Port	N/A
Built-in Mic	Support
Built-in Speaker	N/A

WIFI	N/A
Network	1 × RJ45 10 M/100 M Base-TX Ethernet
Video Output	N/A
Certification	
EMC	CE-EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 50130-4) FCC (FCC 47 CFR part15 B)
Safety	CE-LVD (EN 62368-1) UL/CUL (UL 62368-1, CAN/CSA C22.2 No. 62368-1)
Environment	CE-RoHS (2011/65/EU ; (EU) 2015/863) ; WEEE (2012/19/EU)
Protection	IP67 (IEC 60529) IK10 (IEC 62262)
General	
Power	DC 12 V±25%, PoE (IEEE 802.3af)
Power Consumption	Max. 3 W
Power Interface	Ø5.5 mm coaxial power plug
Dimensions	Ø128 mm × 100 mm (Ø5.0" × 3.9") (Ø × H)
Weight	0.51 kg (1.12 lb.)
Material	Metal + Plastic
Working Environment	-30 °C to 60 °C (-22 °F to 140 °F), Humidity: ≤ 95% RH (non-condensing)
Storage Environment	-30 °C to 60 °C (-22 °F to 140 °F), Humidity: ≤ 95% RH (non-condensing)
Surge Protection	4 KV
Reset Button	Support
Web Client Language	14 Languages: English, Simplified Chinese, Polish, German, Russian, French, Korean, Dutch, Czech, Portuguese, Spanish, Spanish (Europe), Italian, Turkish

Dimensions



Accessories

TR-JB03-H-IN-V2	TR-CM24-IN	TR-SE24-A-IN
Turret Junction Box(Support Wiring From Behind)	Dome Pendant Mounting Bracket(Indoor)	Dome Pendant Mounting Pole 500mm
		
TR-SE24-IN	TR-A01-IN	TR-UC08-C-V2
Dome Pendant Mounting Pole 200mm	NPT 3/4" Waterproof Cable Gland	Bullet&Dome Corner Mounting Bracket
		

TR-JB07/WM03-F-IN-V2	TR-WM03-B-IN-V2	TR-UP06-C-IN-V2
Wall Mounting Assembling Bracket with Back Hole For 3 Inches Dome	3 Inches Dome Wall Mounting Assembling Bracket	Pole Mounting Bracket For Bullet Junction Box Only
		
HS-207S		
VF Dome Sunshade Shell		
		

Unlimited New View

Zhejiang Uniview Technologies Co., Ltd.



<http://www.uniview.com>



overseasbusiness@uniview.com; globalsupport@uniview.com



No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China



©2026 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.