


## 4MP HD ColorHunter Fixed Bullet Network Camera IPC2314LE-ADF28(40)KM-WL



## Features

- High quality image with 4 MP, 1/1.8" CMOS sensor and F1.0 large aperture lens
- 4 MP (2688 × 1520)@25/20 fps; 4 MP (2560 × 1440)@25/20 fps; 3 MP (2304 × 1296)@30/25 fps; 1080P (1920 × 1080)@30/25 fps
- Ultra 265, H.265, H.264, MJPEG
- ColorHunter technology ensures 24-hour full-color images
- 120 dB true WDR technology enables clear image in strong light scene
- Supports 9:16 corridor mode
- Built-in mic
- White light, up to 30 m (98.4 ft.) white light distance
- MicroSD, up to 512 GB
- IP67 protection
- Supports PoE power supply
- 3-axis


## Specifications

| Model                              | IPC2314LE-ADF28KM-WL                                                                                                                                                                                                                                  |                    | IPC2314LE-ADF40KM-WL |
|------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|----------------------|
| Camera                             |                                                                                                                                                                                                                                                       |                    |                      |
| Max Resolution                     | 4 MP                                                                                                                                                                                                                                                  |                    |                      |
| Sensor                             | 1/1.8" CMOS                                                                                                                                                                                                                                           |                    |                      |
| Min. Illumination                  | Color: 0.0005 Lux (F1.0, AGC ON)                                                                                                                                                                                                                      |                    |                      |
| Shutter                            | Auto/Manual, 1 ~ 1/100000s                                                                                                                                                                                                                            |                    |                      |
| Adjustment Angle                   | Pan: 0° to 360°, Tilt: 0° to 90°, Rotate: 0° to 360°                                                                                                                                                                                                  |                    |                      |
| S/N                                | >52 dB                                                                                                                                                                                                                                                |                    |                      |
| WDR                                | 120 dB                                                                                                                                                                                                                                                |                    |                      |
| Lens                               |                                                                                                                                                                                                                                                       |                    |                      |
| Focal Length                       | 2.8 mm                                                                                                                                                                                                                                                | 4.0 mm             |                      |
| Iris Type                          | Fixed                                                                                                                                                                                                                                                 |                    |                      |
| Iris                               | F1.0                                                                                                                                                                                                                                                  |                    |                      |
| Field of View (H)                  | 111.3°                                                                                                                                                                                                                                                | 88.2°              |                      |
| Field of View (V)                  | 61.2°                                                                                                                                                                                                                                                 | 47.6°              |                      |
| Field of View (D)                  | 131.5°                                                                                                                                                                                                                                                | 104.0°             |                      |
| DORI                               |                                                                                                                                                                                                                                                       |                    |                      |
| DORI Distance (Lens)               | 2.8 mm                                                                                                                                                                                                                                                | 4 mm               |                      |
| DORI Distance (Detect)             | 43.4 m (142.4 ft.)                                                                                                                                                                                                                                    | 62.1 m (203.7 ft.) |                      |
| DORI Distance (Observe)            | 17.4 m (57.1 ft.)                                                                                                                                                                                                                                     | 24.8 m (81.4 ft.)  |                      |
| DORI Distance (Recognize)          | 8.7 m (28.5 ft.)                                                                                                                                                                                                                                      | 12.4 m (40.7 ft.)  |                      |
| DORI Distance (Identify)           | 4.3 m (14.1 ft.)                                                                                                                                                                                                                                      | 6.2 m (20.3 ft.)   |                      |
| Illuminator                        |                                                                                                                                                                                                                                                       |                    |                      |
| Supplemental Light                 | Warm light                                                                                                                                                                                                                                            |                    |                      |
| Light On/Off Control               | Auto/Manual                                                                                                                                                                                                                                           |                    |                      |
| Illumination Distance (Warm Light) | 30 m (98.4 ft.)                                                                                                                                                                                                                                       |                    |                      |
| Video                              |                                                                                                                                                                                                                                                       |                    |                      |
| Video Compression                  | Ultra 265, H.265, H.264, MJPEG                                                                                                                                                                                                                        |                    |                      |
| H.264 Code Profile                 | Baseline profile, Main profile, High profile                                                                                                                                                                                                          |                    |                      |
| Frame Rate                         | Main Stream: 4 MP (2688 × 1520), max. 25 fps; 4 MP (2560 × 1440), max. 25 fps; 3 MP (2304 × 1296), max. 30 fps; 1080P (1920 × 1080), max. 30 fps;<br>Sub Stream: 720P (1280 × 720), max. 30 fps; D1 (720 × 576), max. 30 fps; 640 × 360, max. 30 fps; |                    |                      |
| Video Bit Rate                     | 128 Kbps to 6144 Kbps                                                                                                                                                                                                                                 |                    |                      |
| U-code                             | Support                                                                                                                                                                                                                                               |                    |                      |
| OSD                                | Up to 4 OSDs                                                                                                                                                                                                                                          |                    |                      |
| Privacy Mask                       | Up to 4 areas                                                                                                                                                                                                                                         |                    |                      |
| ROI                                | Support                                                                                                                                                                                                                                               |                    |                      |
| Video Stream                       | Dual streams                                                                                                                                                                                                                                          |                    |                      |
| Image                              |                                                                                                                                                                                                                                                       |                    |                      |
| Smart Illumination                 | Support                                                                                                                                                                                                                                               |                    |                      |

|                         |                                                                                                                                                                                                            |
|-------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| White Balance           | Auto, Outdoor, Fine tune, Sodium lamp, Locked, Auto2                                                                                                                                                       |
| Digital Noise Reduction | 2D/3D DNR                                                                                                                                                                                                  |
| Flip                    | Normal, Flip vertical, Flip horizontal, 180°, 90° Clockwise, 90° Anti-clockwise                                                                                                                            |
| Dewarping               | N/A                                                                                                                                                                                                        |
| HLC                     | Support                                                                                                                                                                                                    |
| BLC                     | Support                                                                                                                                                                                                    |
| Defog                   | Digital defog                                                                                                                                                                                              |
| <b>Events</b>           |                                                                                                                                                                                                            |
| Basic Detection         | Motion detection, Ultra motion detection, Tampering alarm, Audio detection, Cross line (based on human body detection), Intrusion (based on human body detection)                                          |
| General Function        | Watermark, IP address filtering, Access policy, ARP protection, RTSP authentication, User authentication, HTTP authentication                                                                              |
| <b>Audio</b>            |                                                                                                                                                                                                            |
| Audio Compression       | AAC-LC, G.711U, G.711A                                                                                                                                                                                     |
| Audio Bitrate           | G.711U/G.711A: 64 kbps, AAC-LC: 128 kbps                                                                                                                                                                   |
| Two-way Audio           | N/A                                                                                                                                                                                                        |
| Suppression             | Support                                                                                                                                                                                                    |
| Sampling Rate           | G.711U/G.711A: 8 kHz, AAC-LC: 8 kHz, 16 kHz, 48 kHz                                                                                                                                                        |
| <b>Storage</b>          |                                                                                                                                                                                                            |
| Network Storage         | ANR, NAS (NFS)                                                                                                                                                                                             |
| Edge Storage            | MicroSD, up to 512 GB                                                                                                                                                                                      |
| <b>Network</b>          |                                                                                                                                                                                                            |
| Protocols               | IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL/TLS, SNMP, QoS                                                                             |
| Compatible Integration  | ONVIF (Profile S, Profile G, Profile T), API, SDK                                                                                                                                                          |
| User/Host               | Up to 32 users, 2 user levels: administrator and common user                                                                                                                                               |
| Security                | Password Protection, Strong Password, HTTPS Encryption, Export Operation Logs, Basic and Digest Authentication for RTSP, Digest Authentication for HTTP, TLS 1.2, WSSE and Digest Authentication for ONVIF |
| Client                  | EZStation, APP                                                                                                                                                                                             |
| Web Browser             | Plug-in required live view: IE 10+, Chrome 45+, Firefox 52+, Edge 79+, Plug-in free live view: Chrome 57+, Firefox 58+, Edge 16+                                                                           |
| <b>Interface</b>        |                                                                                                                                                                                                            |
| Audio I/O               | N/A                                                                                                                                                                                                        |
| Alarm I/O               | N/A                                                                                                                                                                                                        |
| Serial Port             | N/A                                                                                                                                                                                                        |
| Built-in Mic            | Support                                                                                                                                                                                                    |
| Built-in Speaker        | N/A                                                                                                                                                                                                        |
| WIFI                    | N/A                                                                                                                                                                                                        |
| Network                 | 1 × RJ45 10 M/100 M Base-TX Ethernet                                                                                                                                                                       |
| Video Output            | N/A                                                                                                                                                                                                        |
| <b>Certification</b>    |                                                                                                                                                                                                            |
| EMC                     | CE-EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 55035)                                                                                                                                                |

|                     |                                                                         |
|---------------------|-------------------------------------------------------------------------|
|                     | FCC (FCC 47 CFR part15 B)                                               |
| Safety              | CE LVD (EN 62368-1)                                                     |
|                     | CB (IEC 62368-1)                                                        |
|                     | UL/CUL (UL 62368-1, CAN/CSA C22.2 No. 62368-1)                          |
| Environment         | CE-RoHS (2011/65/EU;(EU)2015/863); WEEE (2012/19/EU);                   |
| Protection          | IP67 (IEC 60529)                                                        |
| <b>General</b>      |                                                                         |
| Power               | DC 12 V±25%, PoE (IEEE 802.3af)                                         |
| Power Consumption   | Max. 5.9 W                                                              |
| Power Interface     | Ø5.5 mm coaxial power plug                                              |
| Dimensions          | 206 mm × 73 mm × 73 mm (8.1" × 2.9" × 2.9") (L × W × H)                 |
| Weight              | 0.47 kg (1.04 lb.)                                                      |
| Material            | Graphene + Metal                                                        |
| Working Environment | -30 °C to 60 °C (-22 °F to 140 °F), Humidity: ≤ 95% RH (non-condensing) |
| Storage Environment | -30 °C to 60 °C (-22 °F to 140 °F), Humidity: ≤ 95% RH (non-condensing) |
| Surge Protection    | 4 KV                                                                    |
| Reset Button        | Support                                                                 |
| Web Client Language | 4 Languages: English, Russian, Spanish, Vietnamese                      |

## Dimensions



Accessories

| TR-JB05-B-IN                                                                      | TR-UP06-C-IN                                                                      | TR-A01-IN                                                                           |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Small Bullet Junction Box(Elegant White)                                          | Pole Mounting Bracket for Bullet Junction<br>Box Only                             | NPT 3/4" Waterproof Cable Gland                                                     |
|  |  |  |

# Unlimited New View

## Zhejiang Uniview Technologies Co., Ltd.



<http://www.uniview.com>



[overseasbusiness@uniview.com](mailto:overseasbusiness@uniview.com); [globalsupport@uniview.com](mailto:globalsupport@uniview.com)



No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China



©2023-2026 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

\*Product specifications and availability are subject to change without notice.

Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.