

Gigabit Ethernet Switches Datasheet

NSW2010-5GT-POE-IN



주요 특징

- Support IEEE802.3 at standard, compatible with IEEE802.3 af by electrical equipment (PD)
- Supports PoE Power up to 30W for each PoE port;
- Auto detect power device; will not burned non-standard PoE device or normal PoE switch;
- Supports port power supply prioritization, guarantee the continuous power supply of key nodes;
- Supports IEEE802.3 x full duplex flow control and Backpressure half duplex flow control;
- Line-speed forwarding, intelligent identification
- Supports storage – and- forward for Data exchange;

사양

Model	NSW2010-5GT-POE-IN
Hardware Specification	
Ports Type	4×1000Mbps PoE ports (RJ45)+1×1000Mbps ports(RJ45)
Switching capacity	10 Gbps
Standards	IEEE802.3, IEEE802.3u, IEEE802.3az, IEEE802.3x, IEEE802.3af, IEEE802.3at
Packet Buffer	1 M bit
Forwarding performance	7.44Mpps
Power Supply	AC: 100 to 240V, 50/60Hz
MAC	2K
PoE Standard	IEEE 802.3af, IEEE 802.3 at
PoE Mode	ModeA (1236)

Max.PoE Power	60W
Max.Power	65W
Cooling Fans	0
Operating Temperature	0°C to 40°C (32°F to 104°F)
Operating Humidity	10% to 90% (noncondensing)
Indicator	PWR: Steady on: AC input is normal Off: No AC input PoE: Off: No PoE power supply Steady on: PoE power supply is normal Flashing: PoE power supply is abnormal LINK/ACT: Off: No link Flashing: Transmitting data
Weight	<1 kg
작업 모드	Default (Normal mode) : All ports can communicate with each other
Dimensions (W×D×H)	140mm x 76.7mm x 27.7mm (5.5"×3"×1.1")

Ordering Info

Product Model	Description
NSW2010-5GT-POE-IN	Ethernet Switch(POE)

Unlimited New View

浙江宇视科技有限公司



<http://www.uniview.com>



overseasbusiness@uniview.com; globalsupport@uniview.com



South Tower, Building 10, Wanlun Science Park, 88 Jiangling Road, Hangzhou, P.R.China



©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

虽然我司试图在本资料中提供准确的信息，但不保证资料的内容不含有技术性误差或印刷性错误，为此我司对本资料中的不准确不承担任何责任。我司保留在没有通知或提示的情况下对本资料的内容进行修改的权利。