
5MP Fixed IR Eyeball Network Camera

IPC3615LB-SF28(40)-A





주요 특징

- 고화질 이미지 (5 MP, 1/3.0" CMOS 센서 사용)
- 5 MP (2592 × 1944)@20 fps; 4 MP (2560 × 1440)@20 fps; 3 MP (2304 × 1296)@20 fps; 1080P (1920 × 1080)@30/25 fps
- Ultra 265, H.265, H.264, MJPEG
- 스마트 IR, 최대 30 m (98.4 ft.) IR 거리
- 주/야간 기능
- 2D/3D DNR (디지털 노이즈 감소)
- IP67 보호
- DC 12 V, PoE (IEEE 802.3af) 전원 공급 장치
- 3-axis

사양

Model	IPC3615LB-SF28-A	IPC3615LB-SF40-A
카메라		
최대 해상도	5 MP	
센서	1/3.0" CMOS	
최저 조도	컬러: 0.01 Lux (F2.1, AGC 켜짐), IR 사용 시 0Lux	
주간/야간	자동 스위치 (ICR) 가 있는 IR 차단 필터	
셔터	Auto/Manual, 1 ~ 1/100000s	
조정 각도	팬: 0° ~ 360°, 틸트: 0° ~ 80°, 회전: 0° ~ 360°	
S/N	>52 dB	
WDR	DWDR	
렌즈		
초점 거리	2.8 mm	4.0 mm
Iris Type	고정	
Iris	F2.1	
화각(수평)	97.0°	79.0°
화각(수직)	52.2°	42.3°
화각(사각)	107.5°	85.1°
DORI		
DORI 거리(렌즈)	2.8 mm	4 mm
DORI 거리(감지)	63.0 m (206.7 ft.)	90.0 m (295.3 ft.)
DORI 거리(관찰)	25.2 m (82.7 ft.)	36.0 m (118.1 ft.)
DORI 거리(인식)	12.6 m (41.3 ft.)	18.0 m (59.1 ft.)


DORI 거리(식별)	6.3 m (20.7 ft.)	9.0 m (29.5 ft.)
조명		
보조 조명	IR	
조명 거리(IR)	30 m (98.4 ft.)	
파장	850 nm	
IR 켜짐/꺼짐 컨트롤	자동/수동	
비디오		
비디오 압축	Ultra 265, H.265, H.264, MJPEG	
H.264 코드 프로파일	Baseline profile, Main profile, High profile	
프레임 속도	메인 스트림: 5 MP (2592 × 1944), 최대 20 fps; 4 MP (2560 × 1440), 최대 20 fps; 3 MP (2304 × 1296), 최대 20 fps; 1080P (1920 × 1080), 최대 30 fps; 서브 스트림: D1 (720 × 576), 최대 30 fps; 640 × 360, 최대 30 fps; 2CIF (704 × 288), 최대 30 fps; CIF (352 × 288), 최대 30 fps	
비디오 비트 전송률	128 Kbps ~ 6144 Kbps	
U-code	지원	
OSD	최대 4개의 OSD	
프라이버시 마스크	최대 4개 영역	
ROI	지원	
비디오 스트림	듀얼 스트림	
이미지		
화이트 밸런스	자동, 야외, 미세 조정, 나트륨등, 잠김, 자동2	

디지털 노이즈 제거	2D/3D DNR
스마트 IR	지원
이미지 회전	보통, 수직 반전, 수평 반전, 180°
디워핑	N/A
HLC	지원
BLC	지원
디포그	디지털 디포그
이벤트	
기본 감지	움직임 감지, 변조 알람
기본 기능	워터마크, IP 주소 필터링, 액세스 정책, ARP 보호, RTSP 인증, 사용자 인증, HTTP 인증
네트워크	
프로토콜	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, UPnP, HTTP, HTTPS, SMTP, QoS, SSL/TLS, SNMP
호환성 통합	ONVIF (Profile S, Profile T) , API, SDK
사용자/호스트	Up to 32 users, 2 user levels: administrator and common user
보안	Password Protection, 강력한 비밀번호, HTTPS Encryption, Export Operation Logs, RTSP용 기본 및 다이제스트 인증, HTTP용 다이제스트 인증, ONVIF용 WSSE 및 다이제스트 인증
고객	EZStation, APP
웹 브라우저	플러그인 필요 라이브 뷰: IE 10+, Chrome 45+, Firefox 52+, Edge 79+, 플러그인 불필요 라이브 뷰: Chrome 57+, Firefox 58+, Edge 16+
인터페이스	
오디오 I/O	N/A

알람 I/O	N/A
시리얼 포트	N/A
내장 마이크	N/A
내장 스피커	N/A
WIFI	N/A
네트워크	1 × RJ45 10 M/100 M Base-TX Ethernet
비디오 출력	N/A
인증	
EMC	CE-EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 55035) FCC (FCC 47 CFR part15 B)
안전성	CE LVD (EN 62368-1) CB (IEC 62368-1) UL/CUL (UL 62368-1, CAN/CSA C22.2 No. 62368-1)
환경	CE-RoHS (2011/65/EU;(EU)2015/863); WEEE (2012/19/EU);
보호	IP67 (IEC 60529)
일반	
전원	DC 12 V±25%, PoE (IEEE 802.3af)
전력 소비량	최대 5.0 W
전원 인터페이스	Ø5.5 mm 동축 전원 플러그
크기	Ø118 mm × 95 mm (Ø4.6" × 3.8") (Ø × H)
무게	0.28 kg (0.62 lb.)
재료	메탈+플라스틱
저장 환경	-30 ℃ ~ 60 ℃ (-22 ℉ ~ 140 ℉), 습도: ≤ 95% RH (비응결)
작업 환경	-30 ℃ ~ 60 ℃ (-22 ℉ ~ 140 ℉), 습도: ≤ 95% RH (비응결)


서지 보호	4 KV
초기화 버튼	N/A
웹 클라이언트 언어	1개 언어: 영어

크기



액세서리

TR-JB03-I-IN	TR-A01-IN	TR-SE24-IN
Junction Box for Turret Camera(Support wiring from behind)	NPT 3/4'' Waterproof Cable Gland	Dome Pendent Mounting Pole 200mm
		

TR-SE24-A-IN	TR-CM24-IN	TR-JB07/WM03-G-IN-V2
Dome Pendent Mounting Pole 500mm	Dome Pendent Mounting Bracket(Indoor)	Wall Mounting Assembling Bracket For 32 Fix-dome&Mini Fix-dome&Plastic Turret Camera
		
TR-WM03-D-IN-V2	**TR-UC08-C-V2**	**TR-UP06-C-IN-V2**
Wall Mounting Bracket for 32 Fix-dome&Mini Fix-dome&Plastic Turret Camera	Bullet&Dome Corner Mounting Bracket	Pole Mounting Bracket for Bullet Junction Box Only
		
TR-WM07P-B		
Dome Wall Mounting Plastic Bracket		
		

Unlimited New View

Zhejiang Uniview Technologies Co., Ltd.

http://www.uniview.com

overseasbusiness@uniview.com; globalsupport@uniview.com

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China

©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.
*Product specifications and availability are subject to change without notice.
© 2022 Zhejiang Uniview Technologies Co., Ltd. 무단 전재 및 재배포 금지. *제품 사양 및 재고는 사전 예고 없이 변경될 수 있습니다.