


OEC-R3H-ES OEC-R3H-ES



Overview

OEC-R3H-ES Wall Mounted Desfire Card Reader is a contactless Desfire IC card reader. It features high receiving sensitivity and low working current, applicable to scenarios such as access control, attendance, etc.

Features


- Supports Wiegand/RS 485 data output.
- Built in buzzer.
- Supports indoor and outdoor application.
- Stability, sensitivity, and responsiveness.
- Supports ISO 14443 A and ISO 14443 B protocols.

Specifications

Model	OEC-R3H-ES
Hardware Specification	
Operating Frequency	125kHz,13.56MHz
Card reader interface	RS-485 Serial Port x1, Wiegand Output x1
Dimensions	128.8*88*25mm
Weight	128g
Mount Method	115*73mm junction box, 86*86mm junction box
Operating Temperature	-30 °C~65 °C
Operating Humidity	10% to 90%
Storage Temperature	-40 °C~65 °C
Indicator	Steady blue: Normal operation;

	Steady green for 1s: Card authentication succeeded; Steady red for 1s: Card authentication failed
Power Consumption	1.28W
Operating Voltage	DC 12V $\pm$ 25%
Operating Current	107mA
Reading Distance	IC card: max. 3cm
Authentication Mode	Card
Protection Level	IP54
DIP Switch	10-bit, bit1-4: RS-485 Address (default 0000, 0=off, 1=on) bit5: Mode Switch (Off=Wiegand, On=RS-485) bit6: Wiegand Protocol (default off=Wiegand 34, on=Wiegand 26) bit7: Termination Resistor (default off=disabled, on=enabled). Enable when RS-485 line is long or at high rate (>1Mbps) bit8: Enable or disable card security function, default off (On: encryption authentication required, read CPU card file content. Off: no encryption verification, only read card physical number) bit9-10: Reserved
Tamper Button	Supported, continuous rapid beep alarm
Physical	
Material	PC
Basic Business	
Reading Time	< 1s
Card Type	Supports Mifare card physical number, Mifare card sector number, EM card physical number, Desfire card physical number, Desfire card file number reading

Dimensions



Unlimited New View

Zhejiang Uniview Technologies Co., Ltd.



<http://www.uniview.com>



overseasbusiness@uniview.com; globalsupport@uniview.com



No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China



©2026 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.