

## UTP Category 5E Cables

### CAB-5E-A



## 사양

Model	CAB-5E-A
<b>Cable</b>	
Rip-cord	Yes
Product model	CAB-5E-A
Product specification	HSYV-5e 4×2×0.50
Ambient temperature	-20°C~60°C
Packing length	305±1 m
Test Standard	YD/T1019-2013
<b>Conductor</b>	
Material	Solid-Bare Copper
Nom.O.D.(mm)	0.5±0.01 mm
DC resistance	≤95 Ω/km
AWG	24
<b>Insulation</b>	
Material	HDPE
Color	Blue/White- Blue,Green/White-Green,Orange/White-Orange,Brown/White-Brown
Diameter	0.9±0.05 mm
Thickness	0.2±0.02 mm
<b>Pitch</b>	
Offset pitch	≤25 mm

Cable pitch	≤140 mm
<b>Sheath</b>	
Tensile strength	>13.5 Mpa
Material	PVC(complies RoHS/REACH)
Thickness	0.55±0.05 mm
Color	Gray(RAL7046)
External O.D.	5.1±0.3 mm
<b>Surface Printing</b>	
Case number	Yes
Color	Black
Print error / Space	1±0.005 m
Letter height	3.0±0.3 mm
<b>Packing</b>	
Twice packing dimension	370mm*460mm*370mm
Once packing dimension	350mm*216mm*350mm
Twice packing quantity	2 cases
Packing	Carton

## Ordering Info

Product Model	Description
CAB-5E-A	Cat5e(UTP),305m,Overseas

### Zhejiang Uniview Technologies Co., Ltd.



<http://www.uniview.com>



[overseasbusiness@uniview.com](mailto:overseasbusiness@uniview.com); [globalsupport@uniview.com](mailto:globalsupport@uniview.com)



No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China



©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

\*Product specifications and availability are subject to change without notice.

\*Despite our best efforts, technical or typographical errors may exist in this document.

Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.