

# Network Video Recorder NVR816 Series



## Features

- Support Ultra 265/H.265/H.264 video formats
- 64/128-channel input
- Support 2-ch HDMI, 1-ch VGA, HDMI at up to 4K(3840x2160) resolution
- HDMI1, HDMI2 and VGA independent outputs provided
- Up to 12 Megapixels resolution recording
- Redundant power supply optional
- Support HDD hot swap with RAID 0, 1, 5, 6, 10, 50, 60 storage scheme configurable
- Support 2 miniSAS Interfaces
- Support 12V power output
- ANR technology to enhance the storage reliability when the network is disconnected
- Support cloud upgrade
- Support N+1 Hot spare


## Specifications

| Model                           | NVR816-64   | NVR816-128 |
|---------------------------------|---|------------|
| <b>Decoding</b>                 |   |            |
| Decoding Format                 | Ultra 265, H.265, H.264   |            |
| Decoding Capability             | 3 x 12MP@25, 4 x 4K@30, 16 x 1080P@30, 32 x 960P@25, 36 x 720P@30, 64 x D1  |            |
| Decoding Capability Description | The resolution of each channel cannot exceed 4096 pixels in length or width, For VGA/HDMI independent output, the VGA live video is output by default. To output the highest resolution video from the HDMI port, please clear the VGA video on the preview page.   |            |
| Audio Compression               | G.711A, G.711U  |            |
| <b>Network</b>                  |   |            |
| Incoming Bandwidth              | 512 Mbps  |            |
| Outgoing Bandwidth              | 512 Mbps  |            |
| Remote Users                    | 128   |            |
| Protocols                       | TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP, NFS, RTSP, 802.1x, IPv6, IPv4  |            |
| Browser (Plugin)                | IE10, IE11, Chrome 45+, Edge 79+, Firefox 52+   |            |
| <b>Video/Audio Input</b>        |   |            |
| IP Video Input                  | 64-ch   | 128-ch     |
| RCA Audio Input                 | 1-ch  |            |
| <b>Video/Audio Output</b>       |   |            |
| HDMI Output                     | 4K (3840 × 2160)/30 Hz, 1920 × 1080/60 Hz, 1920 × 1080/50 Hz, 1600 × 1200/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz  |            |
| VGA Output                      | 1920 × 1080/60 Hz, 1920 × 1080/50 Hz, 1600 × 1200/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz  |            |
| RCA Audio Output                | 1-ch  |            |
| Liveview Display                | VGA:1/4/6/8/9/16/25/36, HDMI1/HDMI2:1/4/6/8/9/16/25/36/64   |            |
| Corridor Mode Screen            | 3/4/5/7/9/10/12/16/32   |            |
| <b>Two-way Audio</b>            |   |            |
| Two-way Audio                   | 1-ch, RCA (Using the audio input and output)  |            |
| <b>Snapshot</b>                 |   |            |
| FTP/Schedule/Event Snapshot     | Full-ch snapshot (max. 4000 × 3000 video resolution, with snapshot resolution same as the video resolution)   |            |
| <b>Recording</b>                |   |            |
| Recording Resolution            | 12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080P/960P/720P/D1/2CIF/CIF  |            |
| Synchronous Playback in Local   | 16-ch   |            |
| <b>Smart</b>                    |   |            |
| VCA Detection by IPC            | Face Detection, Face Comparison, Vehicle Detection, SIP (Intrusion Detection, Cross Line Detection, Enter Area, Leave Area), Ultra Motion Detection (UMD), Temperature Detection (Fire Detection, Smoking Detection, Temperature Measurement, Smoke and Fire Detection), People Counting (People Flow Counting, Crowd Density Monitoring), Video Metadata, Traffic Monitoring |            |
| Smart by NVR                    | In the Smart Card datasheet   |            |

|                                |   |
|--------------------------------|---|
| VCA Search                     | Face Snapshot Search, Face Comparison Search, Motor Vehicle Search, Non-Motor Vehicle Search, Human Body Search, General Search, People Counting Report   |
| Smart by IPC                   | All channels (up to 64 images/s in total)Face Detection, Face Comparison, Vehicle Detection, Temperature Detection, SIP, UMD, Video Metadata, Traffic Monitoring  |
| by NVR                         | In the Smart Card datasheet   |
| Vehicle Picture Library        | Up to 5 vehicle picture libraries, with up to 25,000 vehicle pictures in total  |
| SIP by NVR with normal cameras | In the Smart Card datasheet   |
| Capacity of Snapshot Records   | 3 millions records for face snapshot, 3 millions records for vehicle snapshot, 2 millions records for SIP   |
| <b>Alarm</b>                   |   |
| General Alarm                  | Defocus Detection, Scene Change Detection, Object Left Behind, Object Removed, Auto Tracking, Motion Detection, Tampering, Human Body Detection, Video Loss, Alarm Input, Audio Detection   |
| Alert Alarm                    | IP Conflict, Network Disconnected, Disk Offline, Disk Abnormal, Illegal Access, Hard Disk Space Low, Hard Disk Full, Recording/Snapshot Abnormal, High CPU Temperature, High Motherboard Temperature, Array Damaged, Array Degraded   |
| <b>GUI Language</b>            |   |
| GUI Language                   | 38 languages: Simplified Chinese, Traditional Chinese, English, Vietnamese, Thai, Turkish, Spanish (Latin America), Portuguese (Brazil), Spanish, Portuguese, French, German, Italian, Dutch, Polish, Czech, Hungarian, Slovak, Russian, Hebrew, Arabic, Ukrainian, Estonian, Bulgarian, Greek, Romanian, Danish, Swedish, Norwegian, Finnish, Croatian, Slovenia, Serbia, Korean, Japanese, Latvian, Lithuanian, Persian |
| <b>Hard Disk</b>               |   |
| SATA                           | 16 SATA Interfaces  |
| Capacity                       | Up to 16 TB for each HDD (The maximum HDD capacity varies with environment temperature)   |
| Disk Array Type                | RAID 0, 1, 5, 6, 10, 50, 60   |
| Hot Swap                       | Support   |
| <b>External Interface</b>      |   |
| Network Interface              | 4 RJ45 10 M/100 M/1000 M self-adaptive Ethernet Interface   |
| USB                            | Front panel: 2 × USB2.0, Rear panel: 2 × USB3.0   |
| RS485                          | 1   |
| RS232                          | 1   |
| Alarm In                       | 24-ch   |
| Alarm Out                      | 8-ch  |
| eSATA                          | 1   |
| miniSAS                        | 2   |
| Extension Board                | 2   |
| Power Output                   | 12 V  |
| Power Supply                   | AC 100 to 240 V   |
| Power Switch                   | Support   |
| Redundant Power Supply         | Support   |
| <b>Working Environment</b>     |   |
| Working Temperature            | -10 °C to 55 °C (14 °F to 131 °F)   |

|                                 |  |
|---------------------------------|--|
| Working Humidity                | ≤ 90% RH (non-condensing)                          |
| Power Consumption (without HDD) | ≤ 65W  |
| <b>Dimensions</b>               |  |
| Weight (without HDD)            | ≤ 12.5Kg (27.56lb)                                 |
| Dimensions                      | 482mm × 533mm × 131.0mm (19.0"×21.0"×5.1")         |
| <b>Certification</b>            |  |
| Certification                   | CE; FCC; UL; RoHS; WEEE                            |
| CE                              | EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 55035 |
| FCC                             | Part15 Subpart B                                   |

## Dimensions



## Accessories

**FB-HD04-B-NB**

4-ch HDMI Output Decoding Card



**FB-HD07-B-NB**

7-ch HDMI Output Decoding Card



**DEU1016-B**

16 HDDs 3U Disk Enclosure




SL-A  
Slide Rail



PWR-DC12-350A-IN  
350W Power Accessories Module



## Rear Panel



### Zhejiang Uniview Technologies Co., Ltd.



<http://www.uniview.com>



[overseasbusiness@uniview.com](mailto:overseasbusiness@uniview.com); [globalsupport@uniview.com](mailto:globalsupport@uniview.com)



No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China



©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

\*Product specifications and availability are subject to change without notice.

\*Despite our best efforts, technical or typographical errors may exist in this document.

Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.