

# Unmanaged Ethernet PoE Switches

## NSW2020-16T2GC-POE-IN



## Features


- Multiple working modes to address your business needs: Default (Normal mode), VLAN (Secure mode), EXTEND (Surveillance mode)
- Support port traffic control
- Support for secure mode, all downlink ports can communicate only with uplink ports
- Up to 250m transmission distance on surveillance mode
- Support buffer optimization
- All metal housing, safe and reliable

## Specifications

| Model                  | NSW2020-16T2GC-POE-IN                                  |
|------------------------|--------------------------------------------------------|
| Hardware Specification |                                                        |
| Ports Type             | 16×100Mbps PoE ports (RJ45) +2×1000Mbps Combo ports    |
| Switching capacity     | 7.2 Gbps                                               |
| Packet Buffer          | 4 M bit                                                |
| Forwarding performance | 5.36Mpps                                               |
| Power Supply           | AC: 100 to 240V, 50/60Hz                               |
| MAC                    | 16K                                                    |
| PoE Standard           | IEEE 802.3 at, IEEE 802.3af                            |
| PoE Mode               | ModeA (1236), ModeB (4578)                             |
| Max.PoE Power          | Max capacity:250W<br>Max capacity for single port: 30W |

|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Prior Ports           | 1 to 8                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Standards             | IEEE802.3, IEEE802.3u, IEEE802.3z, IEEE802.3ab, IEEE802.3x, IEEE802.3af, IEEE802.3at, IEEE802.3az                                                                                                                                                                                                                                                                                                                                                                                                   |
| Cooling Fans          | 1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Max.Power             | 265W                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Operating Temperature | 0°C to 45°C (32°F to 113°F)                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Operating Humidity    | 10% to 90% (noncondensing)                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Indicator             | <p>POWER:</p> <p>Steady on: AC input is normal</p> <p>Off: No AC input</p> <p>PoE:</p> <p>Off: No PoE power supply</p> <p>Steady on: PoE power supply is normal</p> <p>PoE-MAX:</p> <p>off : The POE power supply power of the whole machine is less than 80% of the specification</p> <p>Steady on : The POE power supply power of the whole machine is greater than 85% of the specification</p> <p>LINK/ACT:</p> <p>Off: No link</p> <p>Steady on: Linked</p> <p>Flashing: Transmitting data</p> |
| Dimensions (W×D×H)    | 440*190*44mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Weight                | 2.07KG                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Working Mode          | <p>Default (Normal mode) : All ports can communicate with each other, VLAN (Secure mode): Downlink ports can communicate only with uplink ports. Enabling PD keepalive function, the switch will restart the IPC via PoE power when the IPC sends no message in a period of time, Extend (Surveillance mode): Transmission distance up to 250 meters. Downlink ports can communicate only with uplink ports</p>                                                                                     |
| Compliance            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| NDAA Compliant        | Support                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |

# Dimensions



## Zhejiang Uniview Technologies Co., Ltd.

- <http://www.uniview.com>
- [overseasbusiness@uniview.com](mailto:overseasbusiness@uniview.com); [globalsupport@uniview.com](mailto:globalsupport@uniview.com)
- No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China



©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.  
\*Product specifications and availability are subject to change without notice.  
\*Despite our best efforts, technical or typographical errors may exist in this document.  
Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.