

UTP Category 6 CCA Cables (0.56mm)

CAB-LC3100B-CCA-IN



Specifications

Cable	Description
Product model	CAB-LC3100B-CCA-IN
Test Standard	Fluke Test 90m
Packing length	305±1 m
Rip-cord	Yes
Seperator	Yes
Ambient temperature	-20℃~75℃
Conductor	Description
Material	CCA (23%)
AWG	23
Nom.O.D.(mm)	0.56±0.01 mm
Insulation	Description
Material	HDPE
Diameter	1.03±0.03 mm

Color	Blue/White- Blue,Green/White-Green,Orange/White-Orange,Brown/White-Brown
Sheath	Description
Material	PVC
External O.D.	6.0±0.4 mm
Thickness	0.5±0.05 mm
Color	White
Surface Printing	Description
Letter height	3.0±0.3 mm
Print error / Space	1±0.005 m
Color	Black
Packing	Description
Packing	Pallet
Once packing dimension	420mm*205mm*420mm

Ordering Info

Product Model	Description
CAB-LC3100B-CCA-IN	Cat6(UTP),305m,CCA,White

Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2023-2024 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.