

# VS-BM9500-IN Backup Server Datasheet VS-BM9500-IN



#### **Overview**

The VS-BM9500-IN backup management server is intended to meet video data backup requirements in video surveillance applications. The server provides backup management, Automatic Network Replenishment (ANR), on-demand playback functions, meets recording backup requirements in large and medium-sized video surveillance systems, and is widely applicable to industries including safety, finance, transportation, power, energy, education, large industrial parks, buildings, healthcare, etc.

#### **Features**

- Supports recording backup.
- Supports recording forwarding and storage management.
- Supports N+M redundancy for IP SAN.
- Guarded by a daemon to prevent process exceptions effectively.
- Supports NVR recording backup.
- Uses standard IP SAN for data backup and storage.
- Provides fragment-free storage, reliable system, high space utilization.
- Supports manual backup, scheduled backup, alarm-triggered backup.
- Easy configuration, efficient management, lower management cost.
- Linux OS ensures 24/7 stable operation.
- $\bullet \quad \text{Supports multiple network protocols: TCP, RTSP, UDP, HTTP, IGMP, Telnet, ICMP, ARP, SIP, SNMP, FTP, TFTP, ISCSI.}\\$

### **Specifications**

| Model                          | VS-BM9500-IN |
|--------------------------------|--------------|
| foeward and storage capability |              |

1



| foeward and storage capability  | Max. 512-ch@2M                   |  |
|---------------------------------|----------------------------------|--|
| Backup capability               |                                  |  |
| Backup capability               | Max. 256-ch@2M                   |  |
| Hardware Parameters             |                                  |  |
| AC Power Input Interface (PSU0) | 100-240 V AC; 50 Hz/60 Hz        |  |
| Expansion Power Module Slot     | 1 x 300W power module (standard) |  |
| (PSU1)                          | 1+1 redundancy (optional)        |  |
| Network Interface               | GE*7                             |  |
| Serial Interface                | 1 x RS232, 1 x RS232/RS485       |  |
| USB Interface                   | 4                                |  |
| HDD                             | 1TB                              |  |
| RAM                             | 16GB                             |  |
| HDMI                            | 1                                |  |
| VGA                             | 1                                |  |
| Dimensions (W×D×H)              | 482 mm × 551 mm × 87 mm          |  |
| Weight                          | Standard ≤12kg; maximum ≤14kg    |  |
| Whole-system consumption        | Maximum 150W                     |  |
| Operating temperature           | 0 °C - 40 °C                     |  |
| Operating humidity              | 20%-80% (noncondensing)          |  |

## **Ordering Info**

| Product Model | Description              |
|---------------|--------------------------|
| VS-BM9500-IN  | Backup Management Server |

#### Zhejiang Uniview Technologies Co., Ltd.



http://www.uniview.com



overseasbusiness@uniview.com; globalsupport@uniview.com



No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China (Zhejiang) Pilot Free Trade Zone, China



©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

<sup>\*</sup>Product specifications and availability are subject to change without notice.

<sup>\*</sup>Despite our best efforts, technical or typographical errors may exist in this document.

Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.