

Web-Managed L2 Switch

NSW5100-8GT2GP-IN



Overview

NSW5100 Series are the lite managed switches self-developed by Uniview with high performance. This series supports WEB interface configuration, easy to use and maintain. It supports high-speed backplane bandwidth and uplink fiber optic access. It has powerful Layer 2 network switching capabilities and supports security functions such as access control and storm control. In addition, it provides environmentally-enhanced designs, including environmental monitoring and a wide range of operating temperature between 0 to 45°C, helping users save maintenance costs, simplify network management and create a green and low-carbon network utilization.

Features

- Supports device management on the web interfaces.
- Supports IGMP v1/v2 Snooping, STP/RSTP, ERPS.
- All metal casing, secure and reliable.

Specifications

| Model | NSW5100-8GT2GP-IN |
|------------------------|--|
| Hardware Specification | |
| Ports Type | 8*10/100/1000Mbps RJ45 port, 2*1000Mbps SFP port |
| Switching capacity | 20 Gbps |
| Forwarding performance | 14.88 Mpps |
| Packet Buffer | 3M bits |
| MAC | 8K |
| Cooling Fans | 0 |
| Max.Power | 10W |
| Power Supply | AC: 100 to 240V, 50/60Hz; |
| Weight | 0.90kg |
| Dimensions (W×D×H) | 280 × 125 × 44 mm |
| Operating Temperature | 0°C to 45°C |
| Operating Humidity | 5% to 95%, non-condensing |
| Indicator | PWR: Steady on: Normal power input Off: Abnormal power input LINK/ACT: Off: The port is disconnected Steady on: The port is connected Blinking: The port is transmitting data |
| Software Specification | |
| Ethernet | Auto-negotiation, 10/100/1000M half-duplex/full-duplex Support port rate adjustment Support port flow control Support link aggregation (Static-LAG & LACP) Support port flow statistics Support port Loopback-detection Support enabling/disabling ports |
| MAC | 8K, auto-learning, auto-update |
| VLAN | Access/Trunk/Hybrid Default VLAN |
| Maintenance | Support a N :1 port mirroring Allow to import, export, back up, and restore factory defaults on the Web interface |
| Security | MAC/IP ACL Mac Limit |
| QoS | Support traffic classification based on DSCP/TOS Support speed limit on ports and streams Support SP, WRR queue scheduling |
| Reliability | Support STP, RSTP, Support ERPS(single ring) |

Multicast

Support IGMP v1/v2 snooping

Unlimited New View

浙江宇视科技有限公司 <http://www.uniview.com> overseasbusiness@uniview.com; globalsupport@uniview.com South Tower, Building 10, Wanlun Science Park, 88 Jiangling Road, Hangzhou, P.R.China

©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

*Despite our best efforts, technical or typographical errors may exist in this document.

Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.