

# Uninterruptible Power Supply UPS800-SEA Series



## Specifications

Model	UPS800-SEA-CEE	UPS800-SEA-UK
<b>Capacity</b>		
Capacity	800 VA	
<b>Input</b>		
Input Voltage	169 VAC to 278 VAC	
Input Current	4 A	
Rated Input Frequency	50 Hz / 60 Hz (Adaptive)	
<b>Output</b>		
Output Voltage	198 VAC to 242 VAC	
Output Current (Mains Supply)	4 A Max	
Output Current (Battery Powered)	50 A Max	
Output Power (Mains Supply)	530 W Max	
Output Power (Battery Powered)	360 W Max	
Output Frequency	50 Hz / 60 Hz (Adaptive)	
Power Factor	0.6	
Switch Time	<10 ms	
Output Wave	Pure Sine Wave (Main Electricity Mode); Square Wave (Battery Mode)	
<b>Battery</b>		
Built-in Battery	Yes	

Battery Type	Lead - Acid Battery	
Qty.of Battery	12 V, 9 Ah × 1	
Charging Current	0.5 - 2 A	
Limited Charge Voltage (Boost Charge)	14.2 ± 0.2 V	
Limited Charge Voltage (Float Charge)	13.6 ± 0.2 V	
Charging Time	4-6 hours recover to 90% capacity	
<b>Status Indicator Light</b>		
Battery Powered	Middle indicator is flashing red (every 6 seconds)	
Mains Supply	Left indicator is green	
Charging while Shutdown	Right indicator is steady yellow	
Charging while On	Right indicator is yellow with breathing effect	
<b>Alarm Indicator</b>		
Low Power	Alarms one sound every 1 second	
Overload	Alarms one sound every 0.5 seconds	
Fault	Continuous Alarm	
<b>Protection</b>		
Short Circuit	Support	
Surge	Support	
Overload	Support	
Heavy Discharge	Support	
Overcharge	Support	
<b>Plugs and Sockets</b>		
Input Plug	European Standard	British Standard
Input Cable Length	1.2 m (47.24 ft.)	
Socket	Universal Socket	
Number of Output Sockets	2	
<b>Structure</b>		
Product Dimensions	312 mm * 122 mm * 195 mm (12.3" * 4.4" * 7.7")	
Packaging Dimensions	392 mm * 142 mm * 205 mm (15.4" * 5.6" * 8.1")	
Casing Material	Iron and Plastic	
Appearance Color	Black	
Net Weight	5.51 Kg (12.15 lbs)	
Weight (Battery Only)	2.44 Kg (5.38 lbs)	
<b>Environment</b>		
Operating Temperature	0 °C to 40 °C (32 °F to 104 °F)	
Operating Humidity	0 to 90% (non-condensing)	
Storage Temperature	0 °C to 40 °C (32 °F to 104 °F)	
Storage Humidity	0 to 90% (non-condensing)	

# Unlimited New View

## Zhejiang Uniview Technologies Co., Ltd.



<http://www.uniview.com>



[overseasbusiness@uniview.com](mailto:overseasbusiness@uniview.com); [globalsupport@uniview.com](mailto:globalsupport@uniview.com)



No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China



©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

\*Product specifications and availability are subject to change without notice.

Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.