

OFG8501N

OFG8501N



Overview

OFG8501N swing barrier gate is specifically designed for pedestrian access control requirements. Equipped with a standard access control board, it supports external card readers and smart recognition devices, seamlessly integrating smart recognition technology to achieve precise access control. Supports multiple verification modes. Featuring a simple and elegant design, it has an internal mechanism manufactured with advanced technology to ensure long-term operational reliability. It can be widely applied in scenarios such as school campuses, industrial parks, residential communities, and residential compounds.

Features

- Standard access control board functionality supports direct connection to card readers.
- All functional components are pre-wired internally at the factory; the gate only requires connection of bridging cables, Ethernet cables, and power cables for operation.
- Supports advanced features including single-lane anti-passback, multi-lane cross-controller anti-passback, and multi-factor verification.
- Enables quick setup via the web interface.
- Supports external Bluetooth speakers for playing gate audio.
- Incorporates an advanced non-destructive transmission mechanism paired with high-quality DC brushless motors, ensuring precise control, stable operation, and extended lifetime.
- Utilizes cutting-edge motor control technology with a closed-loop control system and DSP-based self-regulating motor control, combined with proprietary motor control algorithms for precise positioning and stable performance of the blocking mechanism.
- Comprehensive safety design.
- Implements dual smart anti-pinch protection through advanced infrared sensors and current detection, ensuring complete pedestrian safety.
- All electrical modules operate on safe voltages below 24V, preventing electric shock hazards.
- Motors are installed in the under section of the gate, effectively preventing water damage from rain exposure.


- Supports automatic door opening during power failure for efficient crowd evacuation.
- Features a built-in professional receiver module, supporting 1-to-32 door opening configurations (remote transmitter modules must be purchased separately).
- Allows flexible selection of normal passage modes: keep open or keep closed. Effectively alleviates crowd pressure by adjusting door wing speed based on pedestrian flow, improving operational efficiency.
- Comprehensive infrared functionality:
 - 16 pairs of infrared sensors effectively monitor passage status.
 - Accurately detects reverse passing, tailgating, and other unauthorized intrusions, triggering audible and visual alarms.
 - Alarms can be transmitted via serial port to backend management systems for integration with related systems.
 - Door wings utilize clamp installation for easy disassembly and maintenance.
 - Equipped with self-diagnostic functionality to provide prompt alerts for abnormalities, facilitating user maintenance and operation.
- Other features
 - Supports networked operation and maintenance, meeting specifications for fault diagnosis, event management, access mode configuration, and core mechanism control.
 - Detects the number of people by infrared sensors, uploads data to the platform for statistics, records the number of events such as tailgating, reverse passing, and illegal intrusion, and reports alarms.

Specifications

Model	OFG8501N@L	OFG8501N@M	OFG8501N@R
Structure			
Type	Left pedestal	Middle pedestal	Right pedestal
Core Mechanism			
Motor	Brushless DC motor		
IR Sensor			
IR sensors	16 pairs of infrared sensors: 8 pairs on the upper level, 6 pairs on the lower level, and 2 pairs on the support columns.	16 pairs of infrared sensors: 8 pairs on the upper level, 6 pairs on the lower level, and 2 pairs on the support columns.	16 pairs of infrared sensors: 8 pairs on the upper level, 6 pairs on the lower level, and 2 pairs on the support columns.
Steel Plate Thickness			
Steel plate thickness	Chassis: 1.2 mm, cover: 1.5 mm thick, 304 brushed stainless steel		
Working Parameters			
Card reader panel	Exit Direction	Bi-directional	Entrance Direction
Power consumption	Standby: approx. 35 W, Normal operation: approx. 45 W, Maximum: approx. 136 W		
Ambient temperature	-40°C to 60°C (A heating module is required below -20 °C.)		
Operating humidity	5% to 80%		
Operating voltage	220 V input; 24 V DC/17 A output		
Installation Holes			
Number of installation holes	Standard installation hole(s) for face recognition terminal and decorative cover: one on each side pedestal, two on each middle pedestal		
Door Wing			
Material	Acrylic or stainless steel		

Compatible lane width	Acrylic: 650 mm to 1050 mm(Customization for a width of 1050 mm is supported.) Stainless steel: 650 mm to 1050 mm (Customization for a width of 1050 mm is supported.)		
Appearance Design			
Weight	54KG	58.3KG	56.2KG
Operating environment	Indoor, outdoor		
Dimensions	1506.9 x 970 x 190 mm		
Lane Control Board			
Power	24V		
Lane control board interface	RS485 x 1, alarm input x 1, alarm output x 3, fire alarm interface x 1, IO port x 2, remote controller interface x 2		
Access Control Board			
Power supply	12V		
Card capacity	Normal card: 100,000 Duress card: 1,000 Other types of cards: 100		
Event capacity	200,000		
Communication	Wired communication, Wi-Fi communication		
Permission groups	16		
Time templates	256		
Holiday templates	256		
Anti-passback	Single-lane anti-passback, multi-lane cross-controller anti-passback		
Custom audio	Supports custom modification of default audio		
Abnormal cover opening detection	Supports abnormal cover opening alarm		
Access control board interface	LAN x 2, RS485 x 2, USB x 2, alarm output x 4, exit button input x 2, fire alarm input x 2; Wiegand x 2		
Anti-Pinch			
Anti-pinch	IR anti-pinch, electric current anti-pinch		
Detection			
Anti-tailgating detection distance	5CM tailgating detection		
Anti-reverse passing	Reverse intrusion detection		
Power-off State	Fail-safe (automatically unlocks and opens upon power loss)		
Alarm event			
Alarm event	Sound and light alarm		

Dimensions



Zhejiang Uniview Technologies Co., Ltd.

- <http://www.uniview.com>
- overseasbusiness@uniview.com; globalsupport@uniview.com
- No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China (Zhejiang) Pilot Free Trade Zone, China



©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

*Despite our best efforts, technical or typographical errors may exist in this document.

Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.