

UTP Category 5E Cables (0.50mm)

CAB-LC2100B-IN



Specifications

Cable	Description
Product model	CAB-LC2100B-IN
Packing length	305±1 m
Ambient temperature	-20℃~60℃
Rip-cord	Yes
Conductor	Description
Material	Solid-Bare Copper
AWG	24
Nom.O.D.(mm)	0.5±0.005 mm
DC resistance	≤95 Ω/km
Insulation	Description
Diameter	0.9±0.05 mm
Material	HDPE
Thickness	0.2±0.02 mm
Color	Blue/White- Blue,Green/White-Green,Orange/White-Orange,Brown/White-Brown
Pitch	Description
Offset pitch	≤25 mm
Cable pitch	≤140 mm
Sheath	Description
Material	PVC(complies RoHS/REACH)
Thickness	0.55±0.05 mm
External O.D.	5.1±0.3 mm

Tensile strength	>13.5 Mpa
Color	Gray(RAL7046)
Surface Printing	Description
Color	Black
Letter height	3.0±0.3 mm
Print error / Space	1±0.005 m
Case number	Yes
Packing	Description
Packing	Carton
Once packing dimension	350mm*216mm*350mm
Twice packing dimension	370mm*460mm*370mm

Ordering Info

Product Model	Description
CAB-LC2100B-IN	Cat5e(UTP)-305m-Overseas

Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2024 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.