

UTP Patch Cord Datasheet

GC-CAB6-2m-IN



Features

- Bare Copper conductor
- Excellent performance in the Fluke 100-meter channel test.
- Compliant with RoHS 2.0.
- Stable electrical performance, compliant with TIA-568.2-D, ISO/IEC 11801.
- Suitable for 10BASE-T, 100BASE-TX Fast Ethernet, and 1000BASE-T /1000BASE-TX (Gigabit Ethernet).

Specifications

| | |
|---------------|--------------------------------------|
| Model | GC-CAB6-2m-IN |
| Cable | |
| Product model | U /UTP CAT6 PVC Patch Cord |
| Test Standard | TIA-568.2-D, ISO/IEC 11801, RoHS 2.0 |
| Conductor | |
| Material | Bare Copper (99.95%) |
| Nom.O.D.(mm) | 7*0.16mm±0.005mm, 26AWG |
| Insulation | |
| Material | HDPE |
| Diameter | 0.80±0.05 mm |
| Sheath | |
| Material | PVC |
| Thickness | 0.55 mm±0.05mm |
| External O.D. | 5.5mm±0.3mm |
| Color | Blue(RAL5015) |

Physical

| | |
|--------|----|
| Length | 2m |
|--------|----|

Ordering Info

| Product Model | Description |
|---------------|--|
| GC-CAB6-2m-IN | Cat6 Patch Cord,2m,Blue,Overseas Version |

Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.