

Indoor Station Datasheet

OEI-371S-H-W-NB



Overview

OEI-371S-H-W-NB indoor station is one of the terminals in the digital building intercom system, with functions of video intercom, security alarm, network camera monitoring, etc., providing a safe and comfortable living environment for residents. It can be widely used in building systems such as smart communities, villas, and office parks.

Features

- Durable ABS casing with a glass panel.
- 1024×600 HD touchscreen display.
- Batch configuration and transfer.
- Remote and one-touch unlocking of linked door stations.
- Network camera monitoring and security alarm.

Specifications

Model	OEI-371S-H-W-NB
Hardware Specification	
Operating System	Linux
Power Supply	DC12V±25%,IEEE802.3af, Standard PoE
Power Consumption	<10W
Screen	7-inch ultra-thin TFT LCD screen
Screen Resolution	1024×600
Audio Quality	Noise suppression, echo cancellation and AGC
Audio Input	1 built-in omnidirectional microphone

Audio Output	1 built-in speaker
Audio Compression Standard	MP3 G711
Audio Compression Bitrate	128Kbps
Interface	Power*1, network*1, Wi-Fi*1, RS485*1, IO output*2, IO input*8, TF card slot*1
Network	100Mbps network port, supports IEEE802.3af PoE power supply
Weight	377g
Dimensions (L x W x H)	193.2mm×143.4mm×24.3mm
Operating Environment	-10°C to +55°C, 10% to 90%, non-condensing, indoor
Basic Business	
Network protocol	TCP/IP, IPv4, HTTP, RTP, RTSP, NTP
Specification Index	
Capacity	200 ScreenShots 200 Zone Alarms A total of 20 connected devices, including IPCs, entrance stations, NVRs (up to 2), and Doorbells
Linked Indoor Station Capacity	19 extensions

Ordering Info

Product Model	Description
OEI-371S-H-W-NB	Indoor Station

Accessories

OEP-SP11

Power Emboitement



Dimensions

