

# Ethernet POE Switches Datasheet NSW2020-16T1GT1GC-POE-IN





#### **Features**

- Multiple working modes to address your business needs: Default(Normal mode), VLAN(Secure mode), EXTEND(Surveillance mode)
- Support port traffic control
- Support for secure mode, all downlink ports can communicate only with uplink ports
- Up to 250m transmission distance on surveillance mode
- Support buffer optimization
- All metal housing, safe and reliable

## **Specifications**

Model	NSW2020-16T1GT1GC-POE-IN
Hardware Specification	
Ports Type	16×100Mbps PoE ports (RJ45)+ 1×1000Mbps Gigaethernet ports +1×1000Mbps Combo ports
Switching capacity	7.2 Gbps
Packet Buffer	4 M bit
Forwarding performance	5.36Mpps
Power Supply	AC: 100 to 240V, 50/60Hz
MAC	16K
PoE Standard	IEEE 802.3 at, IEEE 802.3af
PoE Mode	ModeB (4578)
Max.PoE Power	Max capacity:250W
	Max capacity for single port: 30W
Prior Ports	1 to 8


1



Standards	IEEE802.3, IEEE802.3u, IEEE802.3z, IEEE802.3ab, IEEE802.3x, IEEE802.3af, IEEE802.3at, IEEE802.3az
Cooling Fans	1
Max.Power	265W
Operating Temperature	0°C to 45°C (32°F to 113°F)
Operating Humidity	10% to 90% (noncondensing)
	POWER:
	Steady on: AC input is normal
	Off: No AC input
	PoE:
	Off: No PoE power supply
	Steady on: PoE power supply is normal
Indicator	PoE-MAX:
Indicator	off: The POE power supply power of the whole machine is less than 80% of the specification
	Steady on: The POE power supply power of the whole machine is greater than 85% of the
	specification
	LINK/ACT:
	Off: No link
	Steady on: Linked
	Flashing: Transmitting data
Dimensions (W×D×H)	440*195*44mm
Weight	2.12KG
Working Mode	Default (Normal mode): All ports can communicate with each other, VLAN (Secure mode):
	Downlink ports can communicate only with uplink ports. Enabling PD keepalive function, the
	switch will restart the IPC via PoE power when the IPC sends no message in a period of time,
	Extend (Surveillance mode): Transmission distance up to 250 meters. Downlink ports can
	communicate only with uplink ports
Compliance	
NDAA Compliant	Support



## **Dimensions**



#### Zhejiang Uniview Technologies Co., Ltd.



http://www.uniview.com



overseasbusiness@uniview.com; globalsupport@uniview.com



No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China



<sup>\*</sup>Product specifications and availability are subject to change without notice.

<sup>\*</sup>Despite our best efforts, technical or typographical errors may exist in this document.

Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.

