

Disk Enclosure DEU1016-B




Features

- High density. The innovative enclosure with 477mm depth and 3U height that holds up to 16 disks, is space-saving and applicable to the standard rack-mounted scenarios.
- Power protection. Disk powered on sequentially during system startup, protection from impulse current.


Specifications

Model	DEU1016-B
Hard Disk	
SATA	16 SATA Interfaces
Capacity	Up to 24TB for each disk
External Interface	
miniSAS	1
RS232	1
Power Supply	AC 100~240V
Working Environment	
Working Temperature	-10 °C ~ + 55 °C (+14 °F ~ +131 °F)
Working Humidity	5%~95% RH (non-condensing)
Power Consumption (With HDD)	< 160W(With 16 HDDs)
Dimensions	
Weight (Without HDD)	< 10Kg (22lb)
Dimensions	482mm × 477mm× 131mm (19.0"×18.8"×5.1")
Height	3U

Dimensions



Rear Panel



Unlimited New View

Zhejiang Uniview Technologies Co., Ltd.

 <http://www.uniview.com>

 overseasbusiness@uniview.com; globalsupport@uniview.com

 No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China



©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.