

## 2MP ColorHunter HD Fixed Mini Bullet Analog Camera UAC-B122-AF28(40)M-W



### Overview

UAC-B122-AF28(40)M-W is a 2MP ColorHunter HD fixed mini bullet analog camera with a high-performance 1/2.9-inch CMOS sensor. It supports TVI/AHD/CVI/CVBS, which effectively enhances product adaptability and diversity of networking solutions. With SYV-75-3 or other coaxial cable types, the camera can achieve low-cost, long-distance, and anti-interference mega-pixel HD video transmission without time delay. It supports audio input, synchronous transmission of audio and video, and provides 24/7 color images.

### Features


- 2MP high quality imaging
- TVI/AHD/CVI/CVBS
- Supports white light illumination, 24/7 color images
- Supports 180° horizontal flip, 180° vertical flip
- OSD configuration menu, easy to operate
- IP67 waterproof and dustproof design, high reliability
- OSD configuration menu in 11 languages
- Built-in microphone for high quality audio transmission via coaxial cables
- Supports digital defog
- Metal front face and housing

## Specifications

| Model                        | UAC-B122-AF28M-W   | UAC-B122-AF40M-W |
|------------------------------|--|------------------|
| <b>Camera</b>                |  |                  |
| Max Resolution               | 2 MP   |                  |
| Sensor Size                  | 1/2.9" CMOS  |                  |
| Min. Illumination            | 0.005 lux (F1.6, AGC ON)<br>0 lux (white light on)   |                  |
| <b>Lens</b>                  |  |                  |
| Focus                        | 2.8 mm   | 4.0 mm           |
| Lens Mount                   | M12  |                  |
| Angle of View (H)            | 101.5°   | 83.8°            |
| Angle of View (V)            | 56.9°  | 42.7°            |
| Angle of View (D)            | 117.4°   | 100.1°           |
| <b>Illuminator</b>           |  |                  |
| Illuminator Number           | Two white-light illuminators   |                  |
| Illumination Distance        | 40m  |                  |
| Lifetime                     | ≥ 60000 hours  |                  |
| <b>Video</b>                 |  |                  |
| Resolution                   | 1080P: 1920(H)×1080(V)<br>720P: 1280(H) ×720(V)  |                  |
| Frame Rate                   | TVI: 1080P@25fps (default), 1080P@30fps; 720P@25fps, 720P@30fps<br>AHD: 1080P@25fps, 1080P@30fps; 720P@25fps, 720P@30fps<br>CVI: 1080P@25fps, 1080P@30fps; 720P@25fps, 720P@30fps<br>CVBS: PAL, NTSC |                  |
| Shutter Time                 | PAL: 1/25s-1/50000s,<br>NTSC: 1/30s-1/50000s   |                  |
| <b>Image</b>                 |  |                  |
| Exposure Mode                | Four modes: Global (default), BLC, HLC, DWDR   |                  |
| Day/Night                    | 24/7 color images  |                  |
| Digital Noise Reduction      | 2D/3D  |                  |
| White Balance                | Two modes: Auto (default), Manual  |                  |
| WDR                          | DWDR   |                  |
| Flip                         | Supports 180°horizontal flip, 180°vertical flip  |                  |
| Digital Defog                | Support  |                  |
| <b>Audio</b>                 |  |                  |
| Built-in Mic                 | Support  |                  |
| Camera Audio                 | TVI: 1080P@25fps, 1080P@30fps<br>CVI: 1080P@25fps, 1080P@30fps   |                  |
| <b>Interface</b>             |  |                  |
| Power Interface              | 5.5 mm Power Interface   |                  |
| Video Output                 | BNC, supports TVI/AHD/CVI/CVBS   |                  |
| <b>Operating Environment</b> |  |                  |

|                    |  |
|--------------------|--|
| Temperature        | -30 °C to 60 °C (-22 °F to 140 °F)             |
| Humidity           | ≤ 95% RH (non-condensing)                      |
| Surge Protection   | 4kV for power, 4kV for video output interfaces |
| Ingress Protection | IP67   |
| <b>General</b>     |  |
| Power              | DC 12 V ± 25%                                  |
| Power Consumption  | MAX 3.12W                                      |
| Mount              | Corner Mount, Pole Mount                       |
| Dimensions         | 157mm*67mm*66mm (L*W*H)                        |
| Material           | Metal  |
| Weight             | 279g(0.62lb)                                   |

## Dimensions



## Accessories

### TR-A01-IN

NPT 3/4" Waterproof Cable Gland



### TR-JB05-B-IN

Small Bullet Junction Box(Elegant White)



### TR-JB06-IN

Small Bullet Junction Box(Elegant White)



TR-UP06-C-IN-V2

Pole Mounting Bracket for Bullet Junction  
Box Only



TR-UC08-C-V2

Bullet&Dome Corner Mounting Bracket



PWR-DC1201A-UK

DC12V/1A Wall Plug British Standard  
Power Adapter



PWR-DC1201B-UK

UNV DC12V/1A Wall Plug British Standard  
Power Adapter(Colorful Bag)



PWR-DC1201A-US

DC12V/1A Wall Plug American Standard  
Power Adapter



PWR-DC1201B-US

UNV DC12V/1A Wall Plug American  
Standard Power Adapter(Colorful Bag)



PWR-DC1201A-EU

DC12V/1A Wall Plug European Standard  
Power Adapter



PWR-DC1201B-EU

UNV DC12V/1A Wall Plug European  
Standard Power Adapter(Colorful Bag)



PWR-DC1201A-IND

UNV DC12V/1A Wall Plug Indian  
Standard Power Adapter-Colorful Bag



# Unlimited New View

浙江宇视科技有限公司

 <http://www.uniview.com>

 [overseasbusiness@uniview.com](mailto:overseasbusiness@uniview.com); [globalsupport@uniview.com](mailto:globalsupport@uniview.com)

 South Tower, Building 10, Wanlun Science Park, 88 Jiangling Road, Hangzhou, P.R.China



©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

\*Product specifications and availability are subject to change without notice.

虽然我试图在本资料中提供准确的信息，但不保证资料的内容不含有技术性误差或印刷性错误，为此我司对本资料中的不准确不承担任何责任。我司保留在没有通知或提示的情况下对本资料的内容进行修改的权利。