

UTP Category 5E Cables

CAB-5E-B



사양

Model	CAB-5E-B
Cable	
Rip-cord	Yes
Product model	CAB-5E-B
Product specification	HSYV-5e 4×2×0.50
Ambient temperature	-20°C~60°C
Packing length	305±1 m
Test Standard	YD/T1019-2013
Conductor	
Material	Solid-Bare Copper
Nom.O.D.(mm)	0.5±0.01 mm
DC resistance	≤95 Ω/km
AWG	24
Insulation	
Material	HDPE
Color	Blue/White- Blue,Green/White-Green,Orange/White-Orange,Brown/White-Brown
Diameter	0.9±0.05 mm
Thickness	0.2±0.02 mm
Pitch	
Offset pitch	≤25 mm

Cable pitch	≤140 mm
Sheath	
Tensile strength	>13.5 Mpa
Material	PVC(complies RoHS/REACH)
Thickness	0.55±0.05 mm
Color	Gray(RAL7046)
External O.D.	5.1±0.3 mm
Surface Printing	
Case number	Yes
Color	Black
Print error / Space	1±0.005 m
Letter height	3.0±0.3 mm
Packing	
Twice packing dimension	370mm*460mm*370mm
Once packing dimension	350mm*216mm*350mm
Twice packing quantity	2 cases
Packing	Carton

Ordering Info

Product Model	Description
CAB-5E-B	Cat5e(UTP),305m,Overseas

Zhejiang Uniview Technologies Co., Ltd.



<http://www.uniview.com>



overseasbusiness@uniview.com; globalsupport@uniview.com



No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China



©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

*Despite our best efforts, technical or typographical errors may exist in this document.

Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.