

Unmanaged Ethernet PoE Switches

NSW2020-6T-POE-IN-V2



Features

- Multiple working modes to address your business needs: Default (Normal mode), EXTEND (Surveillance mode)
- Support port traffic control
- Support for secure mode, all downlink ports can communicate only with uplink ports
- Up to 250m transmission distance on surveillance mode
- Support buffer optimization
- All metal housing, safe and reliable

Specifications

Model	NSW2020-6T-POE-IN-V2	
Hardware Specification		
Ports Type	6×100Mbps network ports (RJ45), including 4 PoE ports	
Standards	IEEE802.3, IEEE802.3u, IEEE802.3az, IEEE802.3x, IEEE802.3af, IEEE802.3at	
Switching capacity	1.2 Gbps	
Packet Buffer	570K bit	
Forwarding performance	0.90Mpps	
MAC	2К	
Prior Ports	1 to 2	
Power Supply	AC100-240V, 50/60Hz	

UNV

DATASHEET

Max.PoE Power	Max capacity:65W
	Max capacity for single port: 30W
	802.3at/af
	Mode A: (1/2+, 3/6-),
	Mode B: (4/5+, 7/8-)
Storage Temperature	-40 ℃ to 70 ℃
Operating humidity	10%~90% (non-condensing)
Cooling Fans	0
Weight	0.65KG
Dimensions (W×D×H)	169*132*40mm
Storage humidity	5%~90% (non-condensing)
Operating temperature	0 °C to 40 °C (32 °F to 104 °F)
Indicator	POWER Off: No AC input, Power On (Green): Normal power input, Power On (Yellow): The total
	PoE power is higher than 85% of the total power of the device,
	No PoE Indicator, LINK/ACT Off: No link, LINK/ACT Steady on: Linked, LINK/ACT Flashing:
	Transmitting data
Working Mode	Default (Normal mode) : All ports can communicate with each other, EXTEND (Surveillance
Working Mode	mode): Transmission distance up to 250 meters
Max.Power	75W

Ordering Info

Product Model	Description
NSW2020-6T-POE-IN-V2	UNV NSW2020-6T-POE-IN-V2 Unmanaged Ethernet Switch(PoE)

Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China (Zhejiang) Pilot Free Trade Zone, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

http://www.uniview.com

©2024-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such

errors and reserves the right to change the contents of this document without prior notice.