


Double Doors Recognition Access Control Controller

OER-SR22



Overview

OER-SR22 are high-performance and highly reliable access controllers. The products provide TCP/IP wired network communication interfaces and specialized access control and management functions to fit various complex access control scenarios.

Features

- TCP/IP communication with secure reliability.
- Large capacity: Supports up to 42,000 cards and 200,000 events.
- Different mounting holes for easy installation.
- Supports remote upgrade.
- Supports real-time monitoring configuration.
- Supports issuing cards using card readers.

Specifications

Model	OER-SR22
Hardware Specification	
Dimensions (L x W x H)	235mm x 305mm x 76mm
Weight	2.2KG
Door Control	2 doors
Card Reader	4
Wiegand Input Interface (Max DC14V Withstand Voltage)	4
Wiegand Format	WG18/26/34/66
Relay Output	2 sets (7A)

Door Magnetic Port	2
Fire Module Expansion Port	1
Operating Environment	Indoor (-10°C to +65°C)
Power Supply	AC 100V to 240V(50Hz or 60Hz)
Mount	Wall mount
Basic Business	
Communication Mode	TCP/IP
Specification Index	
Card Capacity	42000
Event Capacity	200000

Ordering Info

Product Model	Description
OER-SR22	Double Doors Recognition Access Control Controller

Accessories

OEC-R3H-M

Wall Mounted Mifare Card Reader



OEA-ML22-280

Double Door Electromagnetic Lock 280KG



OEP-GM6-R

Infrared Induction Switch Button



OEC-R3H-MK

Wall Mounted Mifare Keyboard Card Reader



OEP-GP2

Open Door Button



OEP-GP6

Emergency Exit Button



OEA-ML12-280

Single Door Electromagnetic Lock 280KG



OEP-GM5

Open Door Button



OEK-M11

Mifare Card



Technical drawing of the B-6000 Series 1000mm x 1000mm x 100mm Fire Resistant Safe. The drawing includes five views: front, top, bottom, left side, and right side. Dimensions are provided in millimeters and inches.

Front View: 235mm (9.3") width, 305mm (12.0") height.

Top View: 167mm (6.6") width, 43mm (1.7") height.

Bottom View: 167mm (6.6") width, 43mm (1.7") height.

Left Side View: 79mm (3.1") width, 305mm (12.0") height.

Right Side View: 79mm (3.1") width, 305mm (12.0") height.

Table:


TITLE		DRAWN		DATE		CHECKED		DATE		DESIGNED		DATE		PROJECT		SHEET	
B-6000 Series 1000mm x 1000mm x 100mm Fire Resistant Safe																1 OF 1	

THIS DRAWING AND SPECIFICATION ARE THE PROPERTY OF BULLDOG SAFETY TECHNOLOGIES CO., LLC. AND SHALL NOT BE REPRODUCED OR USED IN ANY MANNER WITHOUT THE WRITTEN PERMISSION OF BULLDOG SAFETY TECHNOLOGIES CO., LLC.

- Supports 100 Mbps unmanaged switches only.

 <http://www.uniview.com>

 overseasbusiness@uniview.com; globalsupport@uniview.com

 No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China



©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

*Despite our best efforts, technical or typographical errors may exist in this document.