
5MP HD 지능형 LightHunter IR VF 돔 네트워크 카메라

IPC3235SB-ADZK-I0





주요 특징

- 5MP, 1/2.7" CMOS 센서로 고화질 이미지 제공
- 5 MP (2880 × 1620)@30/25 fps; 4 MP (2560 × 1440)@30/25 fps; 3 MP (2304 × 1296)@30/25 fps; 1080P (1920 × 1080)@30/25 fps
- Ultra 265, H.265, H.264, MJPEG
- 지능형 경계 보호: 크로스 라인, 침입, 구역 진입, 구역 이탈 감지 포함
- 대상 분류 기반 지능형 침입 방지 시스템으로 나뭇잎, 새, 조명에 의한 오경보를 크게 줄이고 사람, 차량, 비자동차에 정확히 집중
- 지능형 얼굴 캡처
- 지능형 피플 카운팅 및 군중 밀집도 모니터링
- LightHunter 기술로 저조도 환경에서도 초고화질 이미지 보장
- 120dB 트루 WDR 기술로 강한 조명 환경에서도 선명한 이미지 구현

- 9:16 복도 모드 지원
- 내장 마이크
- 알람 I/O: 1/1, 오디오 I/O: 1/1
- 스마트 IR, 최대 40m(131.2ft) IR 거리
- MicroSD, 최대 1TB 지원
- IK10 파손 방지 및 IP67 보호 등급

사양

Model	IPC3235SB-ADZK-I0
카메라	
최대 해상도	5 MP
센서	1/2.7" CMOS
최저 조도	Color: 0.002 Lux (F1.2, AGC ON), 0 Lux with IR
주간/야간	IR-cut filter with auto switch (ICR)
셔터	Auto/Manual, 1 ~ 1/100000s
조정 각도	Pan: 0° to 355°, Tilt: 0° to 80°, Rotate: 0° to 355°
S/N	> 56 dB
WDR	120 dB
렌즈	
초점 거리	2.7 to 13.5 mm
화각(수평)	106.3° to 32.5°
Iris Type	Fixed
아이리스	F1.2
화각(수직)	53.5° to 18.0°


화각(사각)	126.0° to 38.5°
렌즈 유형	Motorized
DORI	
DORI 거리(렌즈)	2.7 to 13.5 mm
DORI 거리(감지)	60.8 m to 303.8 m (199.5 ft. to 996.7 ft.)
DORI 거리(관찰)	24.3 m to 121.5 m (79.7 ft. to 398.6 ft.)
DORI 거리(인식)	12.2 m to 60.8 m (40.0 ft. to 199.5 ft.)
DORI 거리(식별)	6.1 m to 30.4 m (20.0 ft. to 99.7 ft.)
조명	
보조 조명	IR
조명 거리(IR)	40 m (131.2 ft.)
조명 켜기/끄기 제어	Auto/Manual
파장	850 nm
비디오	
비디오 압축	Ultra 265, H.265, H.264, MJPEG
프레임 속도	Main Stream: 5 MP (2880 × 1620), max. 30 fps; 4 MP (2560 × 1440), max. 30 fps; 3 MP (2304 × 1296), max. 30 fps; 1080P (1920 × 1080), max. 30 fps; Sub Stream: 720P (1280 × 720), max. 30 fps; D1 (720 × 576), max. 30 fps; 640 × 360, max. 30 fps; Third Stream: D1 (720 × 576), max. 30 fps; 640 × 360, max. 30 fps; 2CIF (704 × 288), max. 30 fps; CIF (352 × 288), max. 30 fps;
H.264 코드 프로파일	Baseline profile, Main profile, High profile
비디오 비트 전송률	128 Kbps to 16 Mbps
U-code	Support
OSD	Up to 8 OSDs
프라이버시 마스크	Up to 4 areas
ROI	Support

비디오 스트림	Triple streams
이미지	
화이트 밸런스	Auto, Outdoor, Fine tune, Sodium lamp, Locked, Auto2
스마트 IR	Support
디지털 노이즈 제거	2D/3D DNR
이미지 회전	Normal, Flip vertical, Flip horizontal, 180°, 90° Clockwise, 90° Anti-clockwise
디워핑	N/A
HLC	Support
BLC	Support
디포그	Digital defog
지능형	
얼굴 캡처	Support
스마트 침입 방지	Cross line detection, intrusion detection, enter area detection, leave area detection (support false alarm filtering and the classification of human, non-motor vehicle and vehicle)
피플 카운팅	Support people flow counting and crowd density detection
통계 분석	N/A
이벤트	
기본 감지	Motion detection, Ultra motion detection, Tampering alarm, Audio detection
기본 기능	Watermark, IP address filtering, Access policy, ARP protection, RTSP authentication, User authentication, HTTP authentication
오디오	
오디오 압축	G.711U, G.711A, AAC-LC
오디오 비트레이트	G.711U/G.711A: 64 kbps, AAC-LC: 128 kbps
양방향 오디오	Support


억제	Support
샘플링 주파수	G.711U/G.711A: 8 kHz, AAC-LC: 8 kHz, 16 kHz, 48 kHz
저장 장치	
엣지 스토리지	MicroSD, up to 1 TB
네트워크 스토리지	ANR, NAS (NFS)
네트워크	
프로토콜	IPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL/TLS, 802.1x, SNMP, PPPoE
호환성 통합	ONVIF (Profile S, Profile G, Profile T, Profile M), API, SDK
사용자/호스트	Up to 32 users. 3 user levels: administrator, common user and operator
보안	Password Protection, Strong Password, HTTPS Encryption, Export Operation Logs, Basic and Digest Authentication for RTSP, Digest Authentication for HTTP, TLS 1.2, WSSE and Digest Authentication for ONVIF
고객	EZStation, APP
웹 브라우저	Plug-in required live view: IE 10+, Chrome 45+, Firefox 52+, Edge 79+, Plug-in free live view: Chrome 57+, Firefox 58+, Edge 16+
인터페이스	
오디오 I/O	1 Input: impedance 35 kΩ, amplitude 2 V [p-p], 1 Output: impedance 600 Ω, amplitude 2 V [p-p]
알람 I/O	1/1
시리얼 포트	N/A
내장 마이크	Support
내장 스피커	N/A
WIFI	N/A
네트워크	1 × RJ45 10 M/100 M Base-TX Ethernet
비디오 출력	N/A

인증	
EMC	CE-EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 55035) FCC (FCC 47 CFR part15 B)
안전성	CE LVD (EN 62368-1) CB (IEC 62368-1) UL/CUL (UL 62368-1, CAN/CSA C22.2 No. 62368-1)
환경	CE-RoHS (2011/65/EU;(EU)2015/863); WEEE (2012/19/EU);
보호	IP67 (IEC 60529) IK10 (IEC 62262)
일반	
전원	DC 12 V±25%, PoE (IEEE 802.3af)
전력 소비량	Max. 7.0 W
전원 인터페이스	Ø5.5 mm coaxial power plug
크기	Ø148.0 mm × 111.4 mm (Ø5.8" × 4.4") (Ø × H)
무게	0.97 kg (2.12 lb.)
재료	Metal
작업 환경	-30 ℃ to 60 ℃ (-22 ℉ to 140 ℉), Humidity: ≤ 95% RH (non-condensing)
저장 환경	-30 ℃ to 60 ℃ (-22 ℉ to 140 ℉), Humidity: ≤ 95% RH (non-condensing)
서지 보호	6 KV
초기화 버튼	Support
웹 클라이언트 언어	20 Languages: Traditional Chinese, English, Simplified Chinese, Polish, German, Russian, French, Korean, Dutch, Czech, Portuguese (Europe), Portuguese (Brazil), Japanese, Thai, Turkish, Spanish (Latin America), Spanish (Europe), Hungarian, Italian, Vietnamese

크기



액세서리

TR-JB04-C-IN Dome Junction Box(Support Wiring From Behind)	**TR-FM152-A-IN** In-Ceiling Bracket For Dome	**TR-SM04-IN** Dome Switch Box Adapter
		
TR-A01-IN NPT 3/4'' Waterproof Cable Gland	**TR-UC08-C-V2** Bullet&Dome Corner Mounting Bracket	**TR-JB07/WM04-B-IN-V2** Wall Mounting Assembling Bracket with Back Hole For 4 Inches Dome
		

TR-WM04-IN-V2 4 Inches Dome Wall Mounting Bracket	TR-CM24-IN Dome Pendent Mounting Bracket(Indoor)	TR-SE24-A-IN Dome Pendent Mounting Pole 500mm
		
TR-SE24-IN Dome Pendent Mounting Pole 200mm	**TR-UP06-C-IN-V2** Pole Mounting Bracket For Bullet Junction Box Only	
		

Unlimited New View

Zhejiang Uniview Technologies Co., Ltd.

http://www.uniview.com

overseasbusiness@uniview.com; globalsupport@uniview.com

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China

©2023-2026 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.
*Product specifications and availability are subject to change without notice.
© 2022 Zhejiang Uniview Technologies Co., Ltd. 무단 전재 및 재배포 금지. *제품 사양 및 재고는 사전 예고 없이 변경될 수 있습니다.