

## 4MP HD Intelligent Light and Audible Warning Fixed Eyeball Network Camera

# IPC3614SB-ADF28(40)KMC-I1



## Features

- High quality image with 4 MP, 1/2.9" CMOS sensor
- 4 MP (2688 × 1520)@30/25 (default) fps; 4 MP (2560 × 1440)@30/25 fps; 3 MP (2304 × 1296)@30/25 fps; 1080P (1920 × 1080)@30/25 fps
- Ultra 265, H.265, H.264, MJPEG
- ColorHunter with Wise-ISP technology ensures 24-hour full-color images
- Intelligent perimeter protection, including cross line, intrusion, enter area, leave area detection
- Intelligent intrusion prevention system based on target classification significantly reduces false alarms caused by leaves, birds, and lighting, accurately focusing on humans, vehicles, and non-motorized vehicles
- Intelligent people flow counting and crowd density monitoring
- 130 dB true WDR technology ensures clear image in strong backlight scene
- Supports 9:16 corridor mode
- Built-in mic and speaker
- Smart IR, up to 30 m (98.4 ft) IR distance
- MicroSD, up to 512 GB
- IP67 protection


## Specifications

| Model                              | IPC3614SB-ADF28KMC-I1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                    | IPC3614SB-ADF40KMC-I1 |
|------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|-----------------------|
| Camera                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                    |                       |
| Max Resolution                     | 4 MP                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                    |                       |
| Sensor                             | 1/2.9" CMOS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                    |                       |
| Min. Illumination                  | Color: 0.003 Lux (F1.4, AGC ON), 0 Lux with light                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                    |                       |
| Day/Night                          | IR-cut filter with auto switch (ICR)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                    |                       |
| Shutter                            | Auto/Manual, 1 to 1/100000 s                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                    |                       |
| Adjustment Angle                   | Pan: 0° to 360°, Tilt: 0° to 80°, Rotate: 0° to 360°                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                    |                       |
| S/N                                | > 56 dB                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                    |                       |
| WDR                                | 130 dB                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                    |                       |
| Lens                               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                    |                       |
| Focal Length                       | 2.8 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 4.0 mm             |                       |
| Iris Type                          | Fixed                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                    |                       |
| Iris                               | F1.4                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                    |                       |
| Field of View (H)                  | 101.1°                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 83.1°              |                       |
| Field of View (V)                  | 57.1°                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 45.0°              |                       |
| Field of View (D)                  | 117.7°                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 98.7°              |                       |
| Lens Type                          | Fixed                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                    |                       |
| DORI                               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                    |                       |
| DORI Distance (Lens)               | 2.8 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 4 mm               |                       |
| DORI Distance (Detect)             | 63.0 m (206.7 ft.)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 90.0 m (295.3 ft.) |                       |
| DORI Distance (Observe)            | 25.2 m (82.7 ft.)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 36.0 m (118.1 ft.) |                       |
| DORI Distance (Recognize)          | 12.6 m (41.3 ft.)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 18.0 m (59.1 ft.)  |                       |
| DORI Distance (Identify)           | 6.3 m (20.7 ft.)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 9.0 m (29.5 ft.)   |                       |
| Illuminator                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                    |                       |
| Supplemental Light                 | Dual light                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                    |                       |
| Illumination Distance (IR)         | 30 m (98.4 ft.)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                    |                       |
| Illumination Distance (Warm Light) | 30 m (98.4 ft.)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                    |                       |
| IR On/Off Control                  | Auto/Manual                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                    |                       |
| Wavelength                         | 850 nm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                    |                       |
| Light On/Off Control               | Auto/Manual                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                    |                       |
| Video                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                    |                       |
| Video Compression                  | Ultra 265, H.265, H.264, MJPEG                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                    |                       |
| H.264 Code Profile                 | Baseline profile, Main profile, High profile                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                    |                       |
| Frame Rate                         | Main Stream: 4 MP (2688 × 1520), max. 30 fps; 4 MP (2560 × 1440), max. 30 fps; 3 MP (2304 × 1296), max. 30 fps; 1080P (1920 × 1080), max. 30 fps; 720P (1280 × 720), max. 30 fps;<br>Sub Stream: 1080P (1920 × 1080), max. 30 fps; 720P (1280 × 720), max. 30 fps; D1 (720 × 576), max. 30 fps; 640 × 360, max. 30 fps; 2CIF (704 × 288), max. 30 fps; CIF (352 × 288), max. 30 fps;<br>Third Stream: D1 (720 × 576), max. 30 fps; 640 × 360, max. 30 fps; 2CIF (704 × 288), max. 30 fps; CIF (352 × 288), max. 30 fps; |                    |                       |

|                            |                                                                                                                                                                                      |
|----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Video Bit Rate             | 128 Kbps to 16 Mbps                                                                                                                                                                  |
| U-code                     | Support                                                                                                                                                                              |
| OSD                        | Up to 8 OSDs                                                                                                                                                                         |
| Privacy Mask               | Up to 4 areas                                                                                                                                                                        |
| ROI                        | Support                                                                                                                                                                              |
| Video Stream               | Triple streams                                                                                                                                                                       |
| <b>Image</b>               |                                                                                                                                                                                      |
| White Balance              | Auto, Outdoor, Fine tune, Sodium lamp, Locked, Auto2                                                                                                                                 |
| Digital Noise Reduction    | 2D/3D DNR                                                                                                                                                                            |
| Smart IR                   | Support                                                                                                                                                                              |
| Flip                       | Normal, Flip vertical, Flip horizontal, 180°, 90° Clockwise, 90° Anti-clockwise                                                                                                      |
| Dewarping                  | N/A                                                                                                                                                                                  |
| HLC                        | Support                                                                                                                                                                              |
| BLC                        | Support                                                                                                                                                                              |
| Defog                      | Digital defog                                                                                                                                                                        |
| <b>Intelligent</b>         |                                                                                                                                                                                      |
| Smart Intrusion Prevention | Cross line detection, intrusion detection, enter area detection, leave area detection (support false alarm filtering and the classification of human, non-motor vehicle and vehicle) |
| Statistical Analysis       | N/A                                                                                                                                                                                  |
| People Counting            | Support people flow counting and crowd density monitoring                                                                                                                            |
| <b>Events</b>              |                                                                                                                                                                                      |
| Basic Detection            | Motion detection, Ultra motion detection, Tampering alarm, Audio detection                                                                                                           |
| General Function           | Watermark, IP address filtering, Access policy, ARP protection, RTSP authentication, User authentication, HTTP authentication                                                        |
| <b>Audio</b>               |                                                                                                                                                                                      |
| Audio Compression          | G.711U, G.711A                                                                                                                                                                       |
| Audio Bitrate              | 64 Kbps                                                                                                                                                                              |
| Two-way Audio              | Support                                                                                                                                                                              |
| Suppression                | Support                                                                                                                                                                              |
| Sampling Rate              | 8 kHz                                                                                                                                                                                |
| <b>Storage</b>             |                                                                                                                                                                                      |
| Edge Storage               | MicroSD, up to 512 GB                                                                                                                                                                |
| Network Storage            | ANR, NAS (NFS)                                                                                                                                                                       |
| <b>Network</b>             |                                                                                                                                                                                      |
| Protocols                  | IPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, SSL/TLS, SSH                                  |
| Compatible Integration     | ONVIF (Profile S, Profile G, Profile T, Profile M), API, SDK                                                                                                                         |
| User/Host                  | Up to 32 users. 3 user levels: administrator, common user and operator                                                                                                               |
| Client                     | EZStation, APP                                                                                                                                                                       |
| Web Browser                | Plug-in required live view: IE 10+, Chrome 45+, Firefox 52+, Edge 79+, Plug-in free live view: Chrome 57+, Firefox 58+, Edge 16+                                                     |
| <b>Interface</b>           |                                                                                                                                                                                      |
| Audio I/O                  | N/A                                                                                                                                                                                  |

|                      |                                                                                                                                                                                                                                                                     |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Alarm I/O            | N/A                                                                                                                                                                                                                                                                 |
| Serial Port          | N/A                                                                                                                                                                                                                                                                 |
| Built-in Mic         | Support                                                                                                                                                                                                                                                             |
| Built-in Speaker     | Support                                                                                                                                                                                                                                                             |
| WIFI                 | N/A                                                                                                                                                                                                                                                                 |
| Network              | 1 × RJ45 10 M/100 M Base-TX Ethernet                                                                                                                                                                                                                                |
| Video Output         | N/A                                                                                                                                                                                                                                                                 |
| <b>Certification</b> |                                                                                                                                                                                                                                                                     |
| EMC                  | CE-EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 50130-4)<br>FCC (FCC 47 CFR part15 B)                                                                                                                                                                          |
| Safety               | CE-LVD (EN 62368-1)<br>UL/CUL (UL 62368-1, CAN/CSA C22.2 No. 62368-1)                                                                                                                                                                                               |
| Environment          | CE-RoHS (2011/65/EU; (EU) 2015/863) ; WEEE (2012/19/EU)                                                                                                                                                                                                             |
| Protection           | IP67 (IEC 60529)                                                                                                                                                                                                                                                    |
| <b>General</b>       |                                                                                                                                                                                                                                                                     |
| Power                | DC 12 V±25%, PoE (IEEE 802.3af)                                                                                                                                                                                                                                     |
| Power Consumption    | Max. 11.0 W                                                                                                                                                                                                                                                         |
| Power Interface      | Ø5.5 mm coaxial power plug                                                                                                                                                                                                                                          |
| Dimensions           | Ø111 mm × 98 mm (Ø4.4" × 3.8") (Ø × H)                                                                                                                                                                                                                              |
| Weight               | 0.47 kg (1.04 lb.)                                                                                                                                                                                                                                                  |
| Material             | Metal                                                                                                                                                                                                                                                               |
| Working Environment  | -30 °C to 60 °C (-22 °F to 140 °F), Humidity: ≤ 95% RH (non-condensing)                                                                                                                                                                                             |
| Storage Environment  | -30 °C to 60 °C (-22 °F to 140 °F), Humidity: ≤ 95% RH (non-condensing)                                                                                                                                                                                             |
| Surge Protection     | 4 KV                                                                                                                                                                                                                                                                |
| Reset Button         | N/A                                                                                                                                                                                                                                                                 |
| Web Client Language  | 20 Languages: Traditional Chinese, English, Simplified Chinese, Polish, German, Russian, French, Korean, Dutch, Czech, Portuguese (Europe), Portuguese (Brazil), Japanese, Thai, Turkish, Spanish (Latin America), Spanish (Europe), Hungarian, Italian, Vietnamese |

## Dimensions



## Accessories

### TR-JB03-G-IN

Junction Box for Mini Fix-dome(Support wiring from behind)



### TR-UM06-E-IN

Slant Mounting Bracket for Fixed Dome



### TR-A01-IN

NPT 3/4" Waterproof Cable Gland



### TR-UP06-IN

Universal Pole Mounting Bracket



### TR-SE24-IN

Dome Pendant Mounting Pole 200mm



### TR-SE24-A-IN

Dome Pendant Mounting Pole 500mm



TR-CM24-IN

Dome Pendant Mounting Bracket(Indoor)



TR-JB07/WM03-G-IN-V2

Wall Mounting Assembling Bracket For 32  
Fix-dome&Mini Fix-dome&Plastic Turret  
Camera



TR-WM03-D-IN-V2

Wall Mounting Bracket for 32  
Fix-dome&Mini Fix-dome&Plastic Turret  
Camera



**Zhejiang Uniview Technologies Co., Ltd.**



<http://www.uniview.com>



[overseasbusiness@uniview.com](mailto:overseasbusiness@uniview.com); [globalsupport@uniview.com](mailto:globalsupport@uniview.com)



No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China



©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

\*Product specifications and availability are subject to change without notice.

\*Despite our best efforts, technical or typographical errors may exist in this document.

Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.